SAFETY DATA SHEET



Section 1. Identification

Product name Techniclean 2000

SDS # 459539 **Code** 459539-US03

Relevant identified uses of the substance or mixture and uses advised against

Product use Cleaner.

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Supplier BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: +1-888-CASTROL

EMERGENCY HEALTH

INFORMATION:

+1-800-447-8735

EMERGENCY SPILL +1-800-424-9300 (CHEMTREC USA)

INFORMATION: +1-703-527-3887 (CHEMTREC outside the US)

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the SKIN IRRITATION - Category 2 substance or mixture SERIOUS EYE DAMAGE - Category 1

GHS label elements

Hazard pictograms



Signal word Danger

Hazard statements Causes skin irritation.

Causes serious eye damage.

Precautionary statements

Prevention Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after

handling.

Response Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty

of soap and water. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage Not applicable.

Disposal Not applicable.

azards not otherwise Defatting to the skin.

Hazards not otherwise classified

This product contains complex ionic mixtures within the fluid matrix which are an intrinsic

part of the product and cannot be separated from the fluid matrix. Toxicology testing has shown the ionic-mixture containing products exhibit skin and eye irritation properties that are notably attenuated when compared to the individual acid and base components.

Product name Techniclean 2000 Product code 459539-US03 Page: 1/10

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Alkalis and additives in aqueous solution.

Ingredient name	%	CAS number
retrapotassium pyrophosphate	≤10	7320-34-5
Alcohols, C9-11, ethoxylated	≤5	68439-46-3
poly(oxy-1,2-ethanediyl), α -[(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-, phosphate	≤3	52623-95-7
(2-methoxymethylethoxy)propanol	≤3	34590-94-8
potassium hydroxide	≤0.78	1310-58-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention immediately. Chemical burns must

be treated promptly by a physician.

Skin contact Get medical attention immediately. In case of contact, immediately flush skin with plenty

of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Clean shoes thoroughly before reuse. Chemical burns must be treated

promptly by a physician.

Inhalation If inhaled, remove to fresh air. Get medical attention immediately.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Wash out mouth with water if person is conscious. Get medical attention immediately. Chemical burns must be treated

promptly by a physician.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Specific treatments No specific treatment.

Product nameTechniclean 2000Product code459539-US03Page: 2/10

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

Combustion products may include the following: phosphorus oxides

metal oxide/oxides

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions for fire-fighters

Special protective equipment for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA)

and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Use only with adequate ventilation. Avoid contact of spilled material and runoff with soil and surface waterways.

Product nameTechniclean 2000Product code459539-US03Page: 3/10

Section 7. Handling and storage

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Tetrapotassium pyrophosphate	None.
Alcohols, C9-11, ethoxylated	None.
poly(oxy-1,2-ethanediyl), α -[(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-, phosphate	None.
(2-methoxymethylethoxy)propanol	ACGIH TLV (United States). Absorbed through skin. TWA: 100 ppm 8 hours. Issued/Revised: 9/1994 TWA: 606 mg/m³ 8 hours. Issued/Revised: 9/1994 STEL: 150 ppm 15 minutes. Issued/Revised: 9/1994 STEL: 909 mg/m³ 15 minutes. Issued/Revised: 9/1994 OSHA PEL (United States). Absorbed through skin. TWA: 100 ppm 8 hours. Issued/Revised: 6/1993 TWA: 600 mg/m³ 8 hours. Issued/Revised: 6/1993
potassium hydroxide	ACGIH TLV (United States). C: 2 mg/m³ Issued/Revised: 9/1994

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Product nameTechniclean 2000Product code459539-US03Page: 4/10Version 7.01Date of issue 12/19/2023.Format USLanguage ENGLISH

Section 8. Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection Hand protection**

Chemical splash goggles.

Wear chemical resistant gloves. Recommended: Butyl gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended: half-face mask - inorganic gases/vapor filter (Type B) - particulate filter. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state Liquid. Color Colorless. Odor Not available. Odor threshold Not available.

pΗ 8.75 [Conc. (% w/w): 5%]

Not available. Melting point/freezing point **Boiling point, initial boiling** point, and boiling range

Not available.

Flash point Closed cup: >100°C (>212°F) [Estimated. Water content interferes with flash point

determination.]

Water content interferes with flash point determination.

Evaporation rate Not available.

Product code 459539-US03 **Product name** Techniclean 2000 Page: 5/10 Version 7.01 Date of issue 12/19/2023. Format US Language ENGLISH

Section 9. Physical and chemical properties

Flammability

Lower and upper explosion limit/flammability limit

Vapor pressure

Not applicable. Based on - Physical state

Not available.

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Water	23.8	3.2				

Relative vapor density

Density

>1000 kg/m³ (>1 g/cm³) at 15°C

Solubility(ies)

Not available.

Partition coefficient: n-

octanol/water

Not applicable.

Not available.

Auto-ignition temperature

Ingredient name	°C	°F	Method
(2-methoxymethylethoxy)propanol	207	404.6	EU A.15

Decomposition temperature

Viscosity

Not available. Not available.

voc

5 g/l

Particle characteristics

Median particle size

Not applicable.

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid

High temperatures

Incompatible materials

Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Section 11. Toxicological information

Information on toxicological effects

Information on the likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact Causes serious eye damage.

Skin contact Causes skin irritation.

Inhalation May give off gas, vapor or dust that is very irritating or corrosive to the respiratory

system. May cause irritation to eyes, nose and throat due to exposure to vapor, mists or

fumes.

Ingestion May cause burns to mouth, throat and stomach.

Product name Techniclean 2000 Product code 459539-US03 Page: 6/10

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Adverse symptoms may include the following:

pain watering redness

Skin contact Adverse symptoms may include the following:

irritation redness dryness cracking

Inhalation No specific data.

Ingestion Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

•	
Route	ATE value
Oral	46666.67 mg/kg

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition Not available. coefficient (Koc)

Mobility Liquid. Soluble in water.

Product name Techniclean 2000 Product code 459539-US03 Page: 7/10

Section 12. Ecological information

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according to IMO instruments

Not available.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b)

All components are active or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification SKIN IRRITATION - Category 2

SERIOUS EYE DAMAGE - Category 1

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated

thresholds.

Supplier notification This product does not contain any hazardous ingredients at or above regulated

thresholds.

Product name Techniclean 2000 Product code 459539-US03 Page: 8/10

Section 15. Regulatory information

State regulations

Massachusetts The following components are listed: DIPROPYLENE GLYCOL METHYL ETHER

New Jersey The following components are listed: DIPROPYLENE GLYCOL METHYL ETHER;

(2-METHOXYMETHYLETHOXY) PROPANOL; PROPANOL, 1(or 2)-

(2-METHOXYMETHYLETHOXY)-

Pennsylvania The following components are listed: PROPANOL, (2-METHOXYMETHYLETHOXY)-

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Not determined.

Other regulations

Australia inventory (AllC)

Canada inventory

China inventory (IECSC)

Japan inventory (CSCL)

Korea inventory (KECI)

Philippines inventory

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

At least one component is not listed.

All components are listed or exempted.

(PICCS)

Taiwan Chemical Substances Inventory

(TCSI)

ubstances Inventory

The company, as identified in Section 1, sells this product in the EU in compliance with

the current requirements of REACH.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of issue/Date of 12/19/2023.

revision

Date of previous issue 05/06/2022.

Prepared by Product Stewardship

Key to abbreviations ACGIH = American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet

STEL = Short term exposure limit TWA = Time weighted average

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0,

64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

Product name Techniclean 2000 Product code 459539-US03 Page: 9/10

Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product nameTechniclean 2000Product code459539-US03Page: 10/10