



Product Data

Iloform PS 700

Soluble Forming Fluid

Description

Castrol Iloform™ PS 700 is a specially formulated, water soluble, wax emulsion lubricant suitable for use in a variety of drawing operations. It can be diluted to achieve any desired film thickness and adheres to metals through multiple draws, minimizing the need to re-apply. Iloform PS 700 contains a special wax system developed with properties not found in other lubricants; the waxes have a unique attraction to metal surfaces due to a high degree of polarity possessed by the individual waxes. This allows up to five consecutive reductions with only one application.

Application

Iloform PS 700 is designed for light to medium duty forming applications on ferrous and aluminum alloys. It can be used at 20% to 40% for light duty forming applications and 40% to neat for applications needing additional lubricity. Iloform PS 700 is also compatible on galvanized materials. It is not recommended for yellow metals.

Advantages

- Versatile - for a wide range of applications.
- Provides good in-process corrosion protection to protect the parts.
- Minimizes oily residues and keeps work areas clean.
- Contains no nitrites, heavy metals, chlorine, phenols, or phosphates to meet health and safety requirements.

User Advice

Apply Iloform PS 700 in a thin, uniform film using roll coater, sponge brush, dip, or spray. For uniform dispersion, add water slowly to concentrate while mixing. The most efficient method of application is the pre-coat system. Metal stock pre-coated with Iloform PS 700 may be dried immediately with a forced ambient air dryer. The remaining non-hydroscopic film is ideal for parts storage; however, parts must be dried before stacking. Iloform PS 700 can be removed with mild alkaline cleaners.

NOTE: Always add water slowly to concentrate with mixing. Never add concentrate to water.

Iloform PS 700

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html