



Castrol HD MOTOR OIL 30

Premium Monograde

Description

Castrol HD Motor Oils are premium monograde oils that are engineered for greater protection against thermal breakdown.

Application

Castrol Motor Oil HD 30 is suitable for use in automotive gasoline engines where the manufacturer recommends an API SP or earlier specification SAE 30 monograde lubricant.

Advantages

Castrol HD Motor Oil 30:

- Provides maximum wear protection in warm climates.
- Use HD 30 when ambient temperature is above 40°F/ 4°C.

Typical Characteristics

Name	Method	Units	Castrol Motor Oil HD 30
Density @ 15C, Relative	ASTM D4052	g/ml	0.87
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	10.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	70
Viscosity Index	ASTM D2270	None	126
Pour Point	ASTM D97	°C	-28
Flash Point, PMCC	ASTM D93	°C	237

Product Performance Claims

API SP

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol HD MOTOR OIL 30

01 Mar 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2

Plant Office: 3660 Lakeshore Blvd West, Toronto, ON M8W 1P2 -

Phone 1-800-268-5339 Fax 416-252-7315 Plant Office telephone: 1 800 268-5339 Trade: 1 888 CASTROL Consumer: 1 800 CASTROL Technical Inquiries: 1 800 462-0835

E-mail info@wakefieldcanada.ca Website www.wakefieldcanada.ca www.castrol.com

Page: 2/2