



## Transmax High Mileage

Automatic Transmission Fluid

### Description

Castrol Transmax™ High Mileage Automatic Transmission Fluid is a premium ATF specially formulated for maximum transmission life in high mileage vehicles. Castrol Transmax™ High Mileage ATF has been engineered to help alleviate typical problems experienced by transmissions with over 75,000 miles such as leaks and rough shifts. Newer vehicles will also benefit from this technologically advanced formulation.

### Advantages

- Additional seal conditioners to prevent or help stop leaks
- Extra cleaning agents to reduce varnish and sludge formulation
- Protects against clutch wear
- Restores smooth shifting
- Greater frictional durability provides superior transmission performance
- The most applications amongst high mileage transmission fluids and suitable for use in vehicles as indicated below:

Manufacturer	Specification
Acura	ATF-Z1 (except in CVTs)
Chrysler	ATF+3®, ATF+2®, ATF+®
Ford	MERCON®
General Motors	DEXRON®- III H, II-D, II, DEXRON®; 9986195; Type A, Suffix A (TASA)
Honda	ATF-Z1, ATF DW-1 (except in CVTs)
Hyundai	SP-II, SP-III
Infiniti	Matic-D, Matic-J, Matic-K
Lexus	Type T, T-III, T-IV
Nissan	Matic-D, Matic-J, Matic-K
Toyota	Type T, T-III, T-IV
Volvo	All Specifications

### Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-IIIH or MERCON® type ATF is specified

### Industry Specifications and OEM Approvals

- Meets or Exceeds General Motors DEXRON®-IIIH Requirements
- Meets or Exceeds Ford MERCON® Requirements

## Typical Physical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	36.6
Viscosity at 100°C, cSt	ASTM D-445	8
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	12,000
Pour Point, °C (°F)	ASTM D-97	-48(-54)
Flash Point, °C (°F)	ASTM D-92	180(356)
Specific Gravity, 60°F	ASTM D-1298	0.862
Pounds per Gallon	ASTM D-287	7.18

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

## Additional Information

### Part Numbers and UPCs

#### Packaged Goods

<b>Case Size</b>	6/1 Qt
<b>Case Part No.</b>	06812
<b>Bottle/ Unit UPC</b>	0-79191-02080-7
<b>Case UPC</b>	0-79191-06812-0

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at [www.castrol.com/us](http://www.castrol.com/us). This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

Transmax High Mileage

24 Oct 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)