



Castrol AP Gear 85W-140

Axle Fluid - Multipurpose

Description

Castrol AP Gear 85W-140 is a multipurpose gear oil for use in most trucks, LCV and Passenger cars conventional differentials, non synchronized manual transmissions and steering gears where API GL-5 performance is required. It is not recommended for Eaton, Spicer, Renault or Rockwell transmissions as those manufacturers prefer non EP transmission oils

Advantages

- AP gear lubricants are formulated for high thermal stability, reducing oxidation and deposits.
- Excellent wear protection which exceeds industry requirements prolongs component life.

Typical Characteristics

Name	Method	Units	AP Gear 85W-140
Specific Gravity, 60F	ASTM D1298	g/ml	0.896
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	25.1
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	323
Flash Point, COC	ASTM D92	°C (°F)	231 (448)
Pour Point	ASTM D97	°C (°F)	-21 (-6)

Product Performance Claims

API GL-5/MT-1
SAE J2360
ArvinMeritor O76-A
Mack GO-J

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol AP Gear 85W-140

11 Jan 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com