SAFETY DATA SHEET



Section 1. Identification

Product name Techniclean AS 105

457568 SDS#

457568-US03 Code

Relevant identified uses of the substance or mixture and uses advised against

Product use Cleaner.

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

BP Lubricants USA Inc. Supplier

1500 Valley Road Wayne, NJ 07470

Telephone: +1-888-CASTROL

EMERGENCY HEALTH

INFORMATION:

+1-800-447-8735

EMERGENCY SPILL +1-800-424-9300 (CHEMTREC USA)

INFORMATION: +1-703-527-3887 (CHEMTREC outside the US)

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the

substance or mixture

ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms



Signal word

Hazard statements May be fatal if swallowed and enters airways.

Precautionary statements

Prevention Not applicable.

IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce Response

vomiting.

Store locked up. **Storage**

Disposal Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

classified

Defatting to the skin.

Product name Product code 457568-US03 Page: 1/9 Techniclean AS 105

Version 2.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 3. Composition/information on ingredients

Substance/mixture

Substance

Hydrocarbon solvent

Ingredient name	%	CAS number
Distillates (Petroleum) hydrotreated light	100	64742-47-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and

remove any contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly

before reuse. Get medical attention if symptoms occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Do not induce vomiting. Never give anything by mouth to an unconscious person. If Ingestion

unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical

attention immediately.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Treatment should in general be symptomatic and directed to relieving any effects. Notes to physician

Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal

intubation. Monitor for cardiac dysrhythmias.

No specific treatment. Specific treatments

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising

from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Hazardous combustion

products

None expected.

Special protective actions for fire-fighters

Special protective

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Fire-fighters' protective clothing will only provide limited protection.

Product name Techniclean AS 105 **Product code** 457568-US03 Page: 2/9

Version 2.02 Date of issue 12/19/2023.

Format US

Language ENGLISH

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapor, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Use explosionproof electrical (ventilating, lighting and material handling) equipment. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid prolonged or repeated contact with skin. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid and as a result may induce allergic skin reactions. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Concentrations of mist, fumes and vapors in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Not suitable

Prolonged exposure to elevated temperature

Product name Techniclean AS 105 Product code 457568-US03 Page: 3/9

Version 2.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Distillates (Petroleum) hydrotreated light

ACGIH TLV (United States). [Kerosene] Absorbed through skin.

TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours. Issued/Revised: 1/2003

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection**

Hand protection

Safety glasses with side shields.

Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Wear clothing and footwear that cannot be penetrated by chemicals or oil.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Language ENGLISH

Product name Techniclean AS 105 **Product code** 457568-US03 Page: 4/9 Format US

Section 8. Exposure controls/personal protection

Respiratory protection

Use with adequate ventilation.

In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended: half-face mask - organic vapor filter (Type A).

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state
Color
Color
Colorless.
Odor
Not available.
Not available.
PH
Not applicable.
Melting point/freezing point
Boiling point, initial boiling
Not available.
Not available.

point, and boiling range

Flash point Closed cup: >105°C (>221°F) [Pensky-Martens]

Evaporation rate Not available.

Flammability Not applicable. Based on - Physical state

Lower and upper explosion limit/flammability limit

explosion Not available.

Vapor pressure Not available.

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method

Relative vapor density Not available.

Density <1000 kg/m³ (<1 g/cm³) at 15°C

Solubility(ies)

Media	Result
water	Not soluble

Partition coefficient: n-

Not applicable.

octanol/water

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Kinematic: 2.6 mm²/s (2.6 cSt) at 40°C

Kinematic: 4.1 mm²/s (4.1 cSt) at 20°C

VOC 819.2 g/l

Particle characteristics

Median particle size Not applicable.

Product nameTechniclean AS 105Product code457568-US03Page: 5/9Version 2.02Date of issue 12/19/2023.Format USLanguage ENGLISH

Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions will not occur.

reactions Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

Incompatible materials Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products should

products not be produced.

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name
Distillates (Petroleum) hydrotreated light

Result
ASPIRATION HAZARD - Category 1

Information on the likely

routes of exposure

Routes of entry anticipated: Dermal, Inhalation, Eyes.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Skin contact

No known significant effects or critical hazards.

Inhalation Vapor inhalation under ambient conditions is not normally a problem due to low vapor

pressure.

Ingestion Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.

Ingestion of large quantities may cause nausea and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Inhalation Exposure to high concentrations can cause dizziness, lightheadedness, headache,

nausea and blurred vision. Higher levels may cause unconsciousness.

May be harmful by inhalation if exposure to vapor, mists or fumes resulting from thermal

decomposition products occurs.

Ingestion Adverse symptoms may include the following:

nausea or vomiting

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Long term exposure

Potential immediate Not available.

effects

Potential delayed effects Not available.

Product name Techniclean AS 105 Product code 457568-US03 Page: 6/9

Version 2.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 11. Toxicological information

Potential chronic health effects

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. **Fertility effects** No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Expected to be biodegradable.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

Not available.

Mobility Liquid. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Product code 457568-US03 Product name Techniclean AS 105 Page: 7/9 Format US Language ENGLISH

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according

to IMO instruments

Not available.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory (TSCA 8b)

All components are active or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification ASPIRATION HAZARD - Category 1

SARA 313

Form R - Reporting This product does not contain any hazardous ingredients at or above regulated

requirements thresholds.

Supplier notification This product does not contain any hazardous ingredients at or above regulated

thresholds.

State regulations

MassachusettsNone of the components are listed.New JerseyNone of the components are listed.PennsylvaniaNone of the components are listed.

California Prop. 65

This product does not require a Safe Harbor warning under California Prop. 65.

Other regulations

Australia inventory (AIIC)

Canada inventory

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

(PICCS)

All components are listed or exempted.

Taiwan Chemical Substances Inventory

(TCSI)

Product name Techniclean AS 105 Product code 457568-US03 Page: 8/9

Version 2.02 Date of issue 12/19/2023. Format US Language ENGLISH

Section 15. Regulatory information

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of issue/Date of

revision

Date of previous issue

Prepared by

Key to abbreviations

12/19/2023.

03/16/2023. Product Stewardship

ACGIH = American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet

STEL = Short term exposure limit TWA = Time weighted average

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0,

64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product code 457568-US03 Product name Techniclean AS 105 Page: 9/9

Format US

Language ENGLISH

Version 2.02 Date of issue 12/19/2023.