



## Product Data

# Techniclean™ XHP

High Pressure Spray Cleaner

## Description

Castrol Techniclean™ XHP (previously called CareClean™ XHP) is a specialized cleaning fluid and corrosion inhibitor for extra high pressure spray wash systems. It is specifically designed for use in totally enclosed industrial spray washers operating at 3,500 to 10,000 psi (240 - 690 bar). As a rust preventive, this fluid contains bi-metallic corrosion inhibitors to protect copper heat exchangers, pump parts and other equipment.

## Advantages

- Low foam eliminates foam-outs in spray washers and enhances performance in transfer lines
- Excellent short-term corrosion protection
- Low pH reduces the possibility of skin irritations
- Highly resistant to bacterial and fungal attack

## Typical Characteristics

Description	Test Method	Unit	Techniclean XHP
Appearance of Concentrate	CN-TM-007	-	Clear yellow fluid
Specific Gravity @ 15°C / 60 °F	CN-TM-086	g/ml	1.07 - 1.10
pH of Concentrate	CN-TM-069	-	7.8 – 8.6
pH of Solution @ 3%	CN-TM-069	-	7.5 – 8.5

Subject to usual manufacturing tolerances.

## Recommended Concentrations

Spray: 3 - 5% concentration; ambient to 150° F (65° C)

## Concentration Control

### With Refractometer:

Factor: 1.7

To calculate the concentration of the diluted fluid, multiply the Refractometer reading by the factor to come up with the in-use concentration.

## User Advice

Techniclean XHP is safe to use on ferrous metals. Consult your Castrol Sales Engineer for questions regarding compatibility.

**This product was previously called CareClean XHP. The name was changed in 2015.**

Techniclean™ XHP

12 Oct 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)