

Spheerol SHL 00

Description

Castrol Spheerol[®] SHL 00 (pre 2015 this product was named SHL 00) is a semi-fluid grease formulated in synthetic fluid (PAO) and Lithium Complex thickener.

Application

Spheerol SHL 00 is used for the lubrication of truck wheel hub assemblies where minimal leakage is desired and long service life is essential. Spheerol SHL 00 can help alleviate oil leakage from wheel seals that can damage brake shoes, increase maintenance costs and affect the overall safety of the unit. Spheerol SHL 00 can be utilized in many types of wheel end systems designed for oil and many systems using conventional greases.

Advantages

- Lithium Complex thickener promotes exceptional service life through excellent water resistance, shear stability, and high temperature stability.
- Contains synthetic (PAO) base stocks for low and high temperature performance and stability.
- Extreme pressure and anti-wear additives extend bearing life by protecting against wear, rust, corrosion, and high temperature.

Typical Characteristics

Name	Method	Units	SHL 00
NLGI Grade	-	-	00
Thickener Type	-	-	Lithium Complex
Colour	Visual / ASTM D1500		Blue
Appearance	Visual	-	Semi Fluid
Worked Penetration @77°F	ASTM D217	-	425
Dropping Point	ASTM D2265	°F/°C	400 / 204
4-Ball EP Weld Point	ASTM D2596	kg	500
4-Ball Wear Scar	ASTM D2266	mm	0.4
Timken OK Load	ASTM D2509	-	60
Rust Prevention	ASTM D1743	-	Pass

Subject to usual manufacturing tolerances

Spheerol SHL 00 23 Oct 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600 www.castrol.com/en_us/b2b/home.html