



Product Data

Almaredge™ 70

General Purpose Soluble Oil

Description

Castrol Almaredge™ 70 (previously called Safety-Cool™ 70) is an economical soluble oil for general machining and grinding of ferrous and non-ferrous metals. The concentrate mixes easily with hard or soft water to form a stable white emulsion that provides good wetting and chip settling action. Almaredge 70 is well suited for recirculating central systems where conventional maintenance techniques can prolong the service life of the emulsion.

Advantages

- Mixes easily with water of various hardness, providing a stable emulsion
- The oily residue provides lubrication to fixtures and gauges
- Non-staining to copper and aluminium alloys
- Easy to dispose of by conventional waste treatment methods

Typical Characteristics

Name	Method	Unit	Almaredge 70
Appearance of Dilution	CN-TM-007	-	Milky - white emulsion
pH of Dilution @ 5%	CN-TM-069	-	9.8 – 10.4
Specific Gravity @ 15°C	CN-TM-084	-	0.91 – 0.93

Subject to usual manufacturing tolerances.

Recommended Concentrations

Grinding 4 - 5%
Machining 5 - 8%

Concentration Control

Refractometer Factor = 1.0

To calculate the concentration of the diluted fluid, multiply the Refractometer reading by the factor to come up with the in-use concentration.

User Advice

Almargde 70 is recommended for machining and grinding of ferrous and non-ferrous alloys. Consult your Castrol Account Manager for questions regarding compatibility.

Additional Information

	Chlorine	Nitrites	Phenols
Additives	-	-	-

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called Safety-Cool 70. The name was changed in 2015.

Almargde™ 70

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html