



Product Data

Techniclean™ MP 2

Multi-purpose process cleaner

Description

Castrol Techniclean™ MP 2 (previously called CareClean™ MP2) is an aqueous, mildly alkaline industrial multi-purpose cleaner containing corrosion inhibitors and biodegradable surfactants. The product is designed to be user-friendly and environmentally responsible. It is free of inorganic salts.

Application

Techniclean MP 2 is a multi-purpose process cleaner for precision cleaning of most metals, even sensitive aluminium alloys. It cleans to the most demanding specifications in a wide range of modern equipment, which includes spray and intensive flood wash as well as all types of dip and ultrasonic applications.

Techniclean MP 2 effectively removes soluble oils, light duty neat cutting or forming oils, lubrication oils, soft film corrosion preventives, swarf and general dirt.

Conditions of Use

	Spray	Flood Wash	Dip / Ultrasonic
Concentration Range:	2-5%	2-5%	2-5%
Temperature Range:	50-80 °C 122-176°F	50-80°C 122-176 °F	40-70°C 104-158°F
Spray Pressure:	up to 3 bar / 50 psi	up to 12 bar / 200 psi	n/a

Optimum conditions of use are depending on the detailed application requirements and the amount and nature of the soil being removed.

Advantages

- Leaves a temporary corrosion preventive film on the metal surface – minimises scrap rate which improves productivity
- Emulsified oil separates on standing and can be skimmed off in order to increase bath-life – reduces maintenance and disposal cost
- Free of inorganic salts, no rinsing required – improves parts cleanliness, enables process rationalisation
- Moderate pH-level - improves environment for the workforce
- Versatile, can be used in various applications on most metals and is suitable in hard and soft water – enables possible product consolidation

Typical Characteristics

Name	Method	Units	Techniclean MP 2
Appearance	CN-TM-007	-	Clear yellow liquid
Density @ 15°C	CN-TM-084	g/cm3	1.05 - 1.07
pH (5% solution)	CN-TM-069	-	8.6 - 9.0

Concentration Control

By Titration:

1. Place (pipette) 50 ml sample of Techniclean MP 2 solution into a flask or beaker.
2. Titrate 1.0N sulfuric acid from a burette until reaching 4.6 on the pH meter.
3. The concentration of the Techniclean MP 2 solution in % (v/v) can be calculated by multiplying the volume of 1.0N sulfuric acid in ml by the concentration factor.
4. Prior to running tests on field samples, follow the above method using a sample of known concentration to obtain the concentration factor.

Concentration factor = % known concentration/ml acid needed to reach the end point.

With Hach kit:

The table below reflects values obtained using a Hach alkalinity test kit (Cat. No 23145). For best results, follow the instructions for use provided in the kit.

Concentration %	1	2	3	4	5
Drops	3	5	7	10	13

Refractometer Factor: 2.1

To calculate the concentration of the diluted fluid, multiply the Refractometer reading by the factor to come up with the in-use concentration.

Storage

To avoid product deterioration always keep the container/drum tightly sealed. Store the product in a cool, dry place away from direct sunlight. Prevent exposure to frost and avoid water ingress. For optimum product stability, it is preferable to store the product indoors between 5°C and 45 °C / 41°F and 113°F.

For more details, please refer the product safety data sheet.

This product was previously called CareClean MP2. The name was changed in 2015.

Techniclean™ MP 2

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html