

Product Data

EDGE High Mileage 10W-30

Fluid TITANIUM - Stronger Under Pressure

Description

As your car ages, its engine can lose performance due to friction and wear. Friction can waste up to 10% of engine performance. Aging parts of the vehicle are prone to costly repairs- catalytic converter failure is one of the most common and expensive problems faced by high mileage engines.

Castrol EDGE High Mileage combines the friction fighting properties of **Fluid TITANIUM** in Castrol EDGE that transforms under pressure, with Phosphorus Replacement Technology that helps prevent catalytic converter failure

Castrol EDGE High Mileage with **Fluid TITANIUM Technology**: unlock the true performance of your high mileage engine.

Application

Castrol EDGE High Mileage 10W-30 is suitable for use in vehicles where the manufacturer recommends: 10W-30

Exceeds manufacturer's warranty requirements for applications requiring API SP (Resource Conserving) and ILSAC GF-6.

Advantages

Boosted with Fluid TITANIUM Technology, Castrol EDGE High Mileage helps maximize engine performance and protect engines with over 75K miles.

Castrol EDGE High Mileage:

- Transforms under pressure to reduce friction and maximize engine performance
- Helps reduce level of phosphorus to help prevent catalytic convertor failures
- Reduces leaks, oil burn-off and deposits
- 6x stronger against wear caused by metal-to-metal contact*
- Improves oil film strength by 30%**
- Helps improve fuel economy

^{*} Seq IVA Test vs API Limit

^{**}As tested in the High Frequency Reciprocating Rig Test with and without Fluid Titanium

Typical Characteristics

Name	Method	Units	Castrol EDGE High Mileage 10W-30
Density @ 15C, Relative	ASTM D4052	g/ml	0.85
Viscosity, Kinematic 100C	ASTM D445	mm²/s	10.5
Viscosity, CCS -25C (10W)	ASTM D5293	mPa.s (cP)	3700
Viscosity, Kinematic 40C	ASTM D445	mm²/s	65
Viscosity Index	ASTM D2270	None	151
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	225
Ash, Sulphated	ASTM D874	% wt	0.78

^{*} When choosing oil, please refer to your owner's handbook and the product specifications shown below. May also be suitable for other vehicles.

Product Performance Claims

API SP ILSAC GF-6

EDGE High Mileage 10W-30 07 Apr 2021

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com