



Castrol EDGE Extended Performance 5W-20

Fluid TITANIUM - Stronger Under Pressure

Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. This means the oil has to be stronger to reduce friction and protect the engine.

Castrol EDGE Extended Performance with patented Fluid TITANIUM is Castrol's most advanced engine oil for ultimate performance and endurance. Its unique adaptive strength maximizes engine performance and delivers an unsurpassed level of protection across a variety of driving conditions and temperatures. *

Castrol EDGE Extended Performance with Fluid TITANIUM: 20,000 miles guaranteed. **

*If your vehicle is under warranty or if driving in severe service applications, follow the oil change interval recommended by your manufacturer. Examples of severe service applications would be racing, frequent towing or hauling, excessive idling or commercial use.

**As tested on Castrol's extreme maximum horsepower endurance test versus Castrol EDGE 5W-30.

Application

Castrol EDGE Extended Performance 5W-20 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C5, API SP, ILSAC GF-6 or earlier specification 5W-20 lubricant

Castrol EDGE Extended Performance 5W-20 is suitable for use in vehicles that require a 5W-20 lubricant that meets Chrysler MS 6395, Ford WSS-M2C945-A/ WSS-M2C945-B1 specifications.

Castrol EDGE Extended Performance 5W-20 is approved for use in GM gasoline vehicles that require a 5W-20 lubricant approved to GM dexos1™ Gen 3* specification.

*GM dexos1™ Approved-GEN 3 : D355EHDC082

Advantages

Recommended for severe applications including:

- Towing or hauling
- Frequent short trips or idling
- High performance driving
- Dusty, humid or extreme temperature environment

Typical Characteristics

Name	Method	Units	Castrol EDGE Extended Performance 5W-20
Density @ 15C, Relative	ASTM D4052	g/ml	0.845
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.2
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44
Viscosity Index	ASTM D2270	None	163
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	225
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

ACEA C5
API SP
ILSAC GF-6
Meets Chrysler MS 6395
Meets Ford WSS-M2C945-A/ WSS-M2C945-B1
GM dexos1™ Gen 3

Castrol EDGE Extended Performance 5W-20

14 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com