



Product Data

Hysol MB 20

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ MB 20 is a high performance chlorine and formaldehyde releasing agent free semi-synthetic metalworking fluid. It contains an additive package that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Hysol MB 20 is suitable for large central systems and single sump machines.

Advantages

- Formaldehyde releasing agent free to comply with health and safety regulations
- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Extend fluid life and reduce maintenance and machine downtime regarding good anti-microbiological performance
- Low foam in recommended water conditions
- Excellent anti-corrosion properties to protect machine tools and parts
- Advanced lubricity compounds ensure improved tool life and part quality
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components

Characteristics

	Unit	Test Method	Value
Appearance of Concentrate	Visual	CN-TM-007	Clear to Slt hazy amber liquid
Appearance of Dilution	Visual	CN-TM-027	Semi-translucent
Specific Gravity @ 15C	-	CN-TM-084	0.987
pH, DI water	-	CN-TM-069	9.4

Recommended Concentrations

Grinding 4 – 5%

Machining 5 – 8%

Water range 100-600 ppm CaCO₃

Concentration Control

% Concentration

3.0

5.0

7.0

10.0

Refractometer Reading

1.8

2.9

4.1

5.9

Additional Information

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	ü	-	-	ü	-

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress. Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Hysol MB 20
12 Jan 2018
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600
www.castrol.com/en_us/b2b/home.html