



## EDGE Supercar 5W-50

Boosted with Fluid Titanium Technology - Strength for Maximum Performance

### Description

Over the past 10 years, supercar engine pressures have almost doubled. Generating phenomenal amounts of horsepower, nothing tests the engine and ultimately the oil like a supercar.

Castrol EDGE SUPERCAR boosted with **Fluid TITANIUM Technology** is proven and tested in supercars, the pinnacle of automotive engineering, and is suitable for use in high performance cars.

Castrol EDGE SUPERCAR is the ultimate proof that our oils are tested to the limits, making them ready to perform however the engine and driver demands.

### Application

Castrol EDGE SUPERCAR 5W-50 is recommended for the FORD GT supercar. Ford GT engine was tested and developed with Castrol EDGE Supercar.

Castrol EDGE SUPERCAR 5W-50 is approved for use in vehicles where the manufacturer requires a product that Meets Ford WSS-M2C931-C. The It has been exclusively developed for the FORD GT supercar and is also suitable for use in other performance cars.

Castrol EDGE SUPERCAR 5W-50 is suitable for use in vehicles where the manufacturer recommends an API SN 5W-50 lubricant.

Please refer to your owners handbook.

### Advantages

Castrol EDGE SUPERCAR 5W-50, boosted with **Fluid TITANIUM Technology** that gives you the confidence to demand maximum engine performance from supercars, sports cars, competition and the latest technology high powered engines which operate under higher pressures requiring an oil with outstanding strength and performance credentials.

Castrol EDGE SUPERCAR 5W-50:

- Maximizes short and long term engine performance
- Reduces engine deposits to help maximize engine response\*
- Delivers outstanding levels of protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure
- Delivers very strong low foam performance
- Proven and tested in world leading supercars

\* Compared to the limit in the ASTM D 6593 Seq VG test

## Typical Characteristics

Name	Method	Units	Castrol EDGE SUPERCAR 5W-50
Density @ 15C, Relative	ASTM D4052	g/ml	0.853
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	16.7
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	5800
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	102
Viscosity Index	ASTM D2270	None	177
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	220
Ash, Sulphated	ASTM D874	% wt	0.78

## Product Performance Claims

API SN

Meets Ford WSS-M2C931-C

EDGE Supercar 5W-50

18 Aug 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)