



Go! 4T 20W-50

With TRIZONE Technology™ – Trouble-Free Ride

Description

Castrol GO! 4T is a high quality engine oil designed for 4-stroke motorcycles. Developed with Castrol's expertise in motorcycle lubricant design, it has Castrol's TRIZONE Technology™ for a trouble-free ride time after time.

Castrol's TRIZONE Technology™ protects the engine, clutch and gears and allows the best functionality of these three critical areas of the motorcycle.

Suitable for all makes of 4-stroke motorcycles, both carburetor or fuel injected. Always follow the vehicle manufacturer's recommendations.

Application

Exceeds industry specifications API SG and JASO MA 2

Advantages

- Provides maximum protection against viscosity and thermal breakdown
- Delivers superior engine wear protection and high film strength for high revving motorcycle engines
- Specialized additives help prevent against ring-sticking and build-up of harmful deposits

Typical Characteristics

Name	Method	Units	Typical Values
Density @ 15C, Relative	ASTM D4052	g/ml	0.886
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.7
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	160
Viscosity Index	ASTM D2270	None	121
Noack Volatility	ASTM D5800	% Loss	4.3
Viscosity, HTHS 150C	ASTM D4683	cP	4.5
Pour Point	ASTM D97	°C	-30

Product Performance Claims

API SG
JASO MA2

Go! 4T 20W-50
12 Nov 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com