



Product Data

Vecton 10W-30 FA-4

Part Synthetic Diesel Engine Oil

Description

NEW CASTROL VECTON 10W-30 FA-4 with unique System Pro Technology™ is our latest technology heavy duty engine oil specifically engineered for fuel economy in selected 2017 and newer diesel engines. It is targeted exclusively at the latest technology, low emission, low fuel consumption trucks and buses where API FA-4 is recommended.

MAIN BENEFITS:

CASTROL VECTON 10W-30 FA-4 delivers **1.0% Fuel Saving*** and extended drain intervals of **up to 60,000 miles and up to 750 hours****

Pumping oil around the engine creates drag which saps engine power and increases the consumption of diesel fuel. Castrol VECTON 10W-30 FA-4 with unique System Pro Technology™ has lower viscosity under high temperature and high shear forces which reduces drag and saves fuel, improving the productivity of the engine.

(* In independent testing vs SAE 15W-40 CJ-4 oil using SAE J1321 test method for class 8 trucks)

(**In combination with and following a proper oil analysis program.)

Application

USER BENEFITS INCLUDE:

New technology developments in diesel engines have led to lower emissions in heavy duty vehicles. These technology advances result in increasing levels of torque within the engine, leading to higher pressures and temperatures. Castrol VECTON 10W-30 FA-4 with unique System Pro Technology™ adapts to increased pressure and temperature with its proven shear stability and oxidation performance:

- Excels under high pressure: engine combustion pressures are increasing, which puts increased pressure on key engine parts. Castrol VECTON 10W-30 FA-4 is formulated to hold its viscosity under high shear contacts to extend oil life
- Performs at high temperature: engine oil is subjected to areas of very high temperature in modern engines, causing oxidation and oil thickening. Castrol VECTON 10W-30 FA-4 is formulated to fight oxidation to extend oil life.

Typical Characteristics

Name	Method	Units	Vecton 10W-30 FA-4
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	cSt	10.1
Viscosity, Kinematic 40C	ASTM D445	cSt	86
Viscosity Index	ASTM D2270		137
Ash, Sulphated	ASTM D874	% w t	1.0
Total Base Number, TBN	ASTM D2896	mg KOH/g	9.5
Pour Point	ASTM D97	°C	-45

Product Performance Claims

API FA-4
Cummins CES 20087
DDC DFS 93K223
Meets Ford WSS-M2C214-B1

Vecton 10W-30 FA-4
20 Dec 2024
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com