



**Product Data**

## **Tribol™ GR TT1 EP**

Low-temperature Greases with MoS2

### **Description**

Castrol Tribol™ GR TT 1 EP (previously called Optitemp TT1 EP) is high performance greases for applications with wide temperature ranges. It is especially suited for rolling and sliding bearings with medium bearing pressures.

Tribol GR TT 1 EP contains MoS2 and is particularly appropriate for extremely high loads

### **Application**

- Rolling and sliding bearings
- Clutch bearings and wheel hubs.
- For bearings running at high speeds with a factor up to about 1 mio.
- Low-temperature application.
- Wide Temperature application range: - 60°C /- 76°F to +120°C/+248°F

### **Advantages**

- Extreme load carrying capacity.
- Optimum wear protection in the high load range.
- Temperature-independent over a wide application range.
- In certain applications can be used for lifetime lubrication.
- Excellent corrosion protection, largely prevents fretting corrosion.
- Anticorrosive.
- Pumpable in centralized lubricating systems.

## Typical Characteristics

Name	Test Method	Units	TT 1 EP
Color	Visual	-	black
Base oil	-	-	Synthetic
Thickener type	-	-	Organic / Inorganic
Density @ 20 °C/68 °F	In house method	kg/m <sup>3</sup>	995
Worked Penetration (60 strokes @ 25 °C/77 °F)	ASTM D217	0.1 mm	310 - 340
Dropping Point	ASTM D566/ISO 2176	°C/°F	240/464
Rust Test- EMCOR (distilled water)	ASTM D6138/ISO 11007	Rating	0
Oil Separation (168 hrs @ 40 °C/104 °F)	IP 121/DIN 51817	%wt	4.30
Flow pressure@ -35°C/-31°F	DIN 51805	hPa	257
Copper Corrosion (24 hrs, 100 °C/212 °F)	ASTM D130/ISO2160	Rating	2b

Subject to usual manufacturing tolerances.

## Additional Information

Please observe the specifications of the bearing manufacturers. TRIBOL GR TT 1 EP is not to be mixed with other greases. Thoroughly clean bearing before introducing the initial fill.

Maximum performance can only be assured if the product is not mixed with other lubricants. Fill bearing housing only about half full with grease.

**This product was previously called Optitemp TT 1 EP. The name was changed in 2015.**

Tribol™ GR TT1 EP

17 Sep 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)