



Castrol EDGE Pick-Up 5W-20 U.S.

Fluid TITANIUM - Stronger Under Pressure

Description

Advances in engine technology have led to increased power and efficiency, meaning engines work harder and under higher pressures than ever before. This means the oil has to be stronger to reduce friction and protect the engine.

Castrol EDGE Pick-Up, engineered with Fluid TITANIUM Technology, provides superior motor oil strength for engines that work harder due to higher engine pressures, helping your vehicle maximize its performance.

Castrol EDGE Pick-Up - Stronger under pressure.

Application

Castrol EDGE Pick-Up 5W-20 U.S. is suitable for use in automotive diesel and gasoline engines of trucks where the manufacturer recommends an ACEA C5, API SP, ILSAC GF-6 or earlier specification 5W-20 lubricant.

Castrol EDGE Pick-Up 5W-20 U.S. is suitable for use in vehicles where a 5W-20 lubricant that meets Ford WSS-M2C945-A, Ford WSS-M2C945-B1, Chrysler MS-6395 specifications 5W-20.

Castrol EDGE Pick-Up 5W-20 U.S. is approved for use in GM vehicles that require a 5W-20 lubricant approved to GM Dexos1TM Gen 3* specification.

*GM Dexos1TM Approved-GEN 3 : D355EIDC082

Recommended for severe applications including:

- Towing or hauling
- Frequent short trips or idling
- High performance driving
- Dusty, humid or extreme temperature environment

Advantages

Castrol EDGE Pick Up 5W-20 U.S. with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's modern vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE Pick Up 5W-20 U.S.

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure

Typical Characteristics

Name	Method	Units	Castrol EDGE Pick Up 5W-20 U.S.
Density @ 15C, Relative	ASTM D4052	g/ml	0.845
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	8.2
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	3500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	44
Viscosity Index	ASTM D2270	None	163
Pour Point	ASTM D97	°C	-39
Flash Point, PMCC	ASTM D93	°C	225
Ash, Sulphated	ASTM D874	% wt	0.78

Product Performance Claims

ACEA C5

API SP

ILSAC GF-6

Meets Chrysler MS 6395

Meets Ford WSS-M2C945-A/ WSS-M2C945-B1

GM dexos1™ Gen 3

Castrol EDGE Pick-Up 5W-20 U.S.

14 Oct 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com