



## Product Data

# Tribol GR 4541 HT

Wide Temperature Range Grease

## Description

High performance Castrol Tribol® GR 4541 HT (previously called Tribol® 4541) Wide Temperature Range Grease is a wide temperature lubricant designed to extend the service life of bearings when loads are moderate to heavy, temperatures are elevated, and speeds are low to moderate. This grease matches the rugged service requirements associated with mills and plants producing engineered woods, primary metals, castings, cement, glass, and paper.

The following performance characteristics were emphasized in the development of Tribol GR 4541 HT:

- Synthetic base fluid for high-temperature stability and low-temperature mobility;
- Optimum viscosity base oil, ISO VG 150, to increase the load carrying capacity;
- Temperature stability to withstand elevated and intermittently high temperatures (dropping point over 260°C/500°F)
- Shear stability to match the anticipated service life of precision anti-friction bearings.

## Application

Tribol GR 4541 HT should be used when loads are moderate to heavy, temperatures are elevated (up to 232°C/450°F), and speeds are slow to moderate. Tribol GR 4541 HT can be used in anti-friction bearings, bushings, and couplings. In addition, the combination of synthetic base fluids provides outstanding low temperature grease mobility.

Establish reapplication intervals by inspection. See Notes regarding temperatures and speeds.

Primary Metals including Steel - Use Tribol GR 4541 HT near hot ingots, soaking pits, and reheat furnaces to lubricate pit cover carriages, mill stand screws, slipper couplings, roll bearings, manipulators and guide rolls for continuous casters.

Use Tribol GR 4541 HT to lubricate bearings that are exposed to both low and high temperatures. These applications include conveyors exposed to both low winter temperatures and the high temperatures associated with foundry and casting operations.

Paper and Forest Products – Use in areas exposed to high temperatures and/or outside winter temperatures.

## Typical Characteristics

Name	Method	Units	Tribol GR 4541 HT
NLGI Grade	-	-	1
Colour	Visual	-	Red
Base Fluid Type	-	-	Fully Synthetic
ISO Grade	-	-	150
Specific Gravity	ASTM D1298 / ISO 3675	-	0.8632
Worked Penetration	ASTM D217	mm/10	310 - 340
Mechanical Stability	points change ASTM D217	100K strokes	+ 11
Oxidation, psi Loss	ASTM D942	100 hrs	5.0
Rust test	ASTM D1543	-	Pass
Water Washout 79°C / 175°F	ASTM D1264	%Loss	5.0
Life Performance	ASTM D3527	hrs	180
Timken OK load	ASTM D2509	lb	50
Four Ball Wear test - Wear Scar Diameter (40 kgf / 75°C / 1200 rpm / 1 hr)	ASTM D2266	mm	0.55
Four Ball EP	ASTM D2596	kg weld	400
Low Temp Torque @ -40°C	ASTM D4178	N. m starting	0.188
Low Temp Torque @ -40°C	ASTM D1478	N. m running	0.09
Lincoln Ventmeter	-	PSI @ - 20°F	810
Leakage tendency	ASTM D4290	g	3.13
Oil Separation	ASTM D1742	%	3.3
Oil Separation 30h, 300°F	FTM 312.2	Total %	5.6

Subject to usual manufacturing tolerances.

**This product was previously called Tribol 4541. The name was changed in 2015.**

Tribol GR 4541 HT

09 Apr 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)