



**Product Data**

## **Tribol™ GR 3020/1000 PD Range**

High performance greases with TGOA

### **Description**

Castrol Tribol™ GR 3020/1000 PD (previously called Tribol 3020/1000) is a range of greases formulated from highly refined petroleum base oils, a lithium thickener, and Tribol Grease Oil Additive (TGOA). The TGOA additive package outperforms all other Extreme Pressure (EP) and Anti-Wear (AW) additives because of its unique action on frictional surfaces.

The base oils are high-viscosity mineral oils forming a stable lubricant film to withstand high continuous loads, shock loads and vibrations. The TGOA additive package is activated by high specific loads and corresponding temperatures causing a chemical physical reaction. This results in an equalisation of surface roughness without creating abrasion.

The results of the TGOA additives can be compared with a rolling process in the micro-range. The surface roughnesses are gradually leveled and smoothed. In smoothing the working surfaces, the loads are distributed over increasing areas and the actual load carrying areas are enlarged. During the running-in process, the TGOA additive package creates an optimum of smooth contact surfaces. If, because of shock loads, or stop-and-go operation, surface roughness peaks redevelop, the TGOA additives are automatically reactivated. Surface roughness is again equalised and lubrication optimised. Corrosion and oxidation inhibitors help maximise effective rust protection and long life of the grease.

The Tribol GR 3020/1000 PD Range contains NLGI consistency grades commonly available for these types of lubricants.

### **Application**

- Applications include large slow-speed bearings where the Tribol 3020/1000 PD greases provide a sufficient lubricating film due to their high base oil viscosity
- Typical applications for Tribol GR 3020/1000 PD fluid greases (NLGI 0) are non-oil-tight gear units, rolling and sliding bearings, bushings, slides and general lubrication designed for fluid-grease lubrication
- Tribol GR 3020/1000 PD grease (NLGI 1 & 2) can be used for roller and sliding bearings, spindles, power train couplings (with exception to high speed precision couplings), carriages, cams and common grease points. They're commonly used in the steel, mineral compound, construction and mining industry
- Operating temperatures range from -40°C to +120°C/ -40°F and +248°F

### **Advantages**

Compared to conventional greases, the Tribol GR 3020/1000 Range provides the following advantages:

- Excellent pumpability in central lubrication systems
- Repairs damaged friction surfaces (roughness) due to the TGOA additives
- Extends lubrication interval
- Reduces wear and noise
- Lowers operating temperatures
- Lowers downtime, therefore reducing maintenance and repair costs
- Optimum sealing effect, due to excellent adhesion of the grease

## Typical Characteristics

Name	Method	Units	Tribol GR 3020/ 1000-2	Tribol GR 3020/ 1000-1	Tribol GR 3020/ 1000-0
Appearance	Visual	-	Homogeneous		
Thickener type	-	-	Lithium	Lithium	Lithium
Base Oil	-	-	Mineral Oil	Mineral Oil	Mineral Oil
Consistency	ISO 2137/ASTM D217	NLGI Grade	2	1	0
Worked Penetration (60 strokes @ 25°C / 77°F)	ISO 2137/ASTM D217	0.1 mm	265 - 295	310 - 340	355 - 385
Dropping Point	ISO 2176/ ASTM D566	°C/°F	>175/ >350	>175/ >350	>160/ >320
Base Oil Viscosity @ 40°C / 104°F	ISO 3104/ ASTM D445	mm <sup>2</sup> /s	1000	1000	1000
Base Oil Viscosity @ 100°C / 212°F	ISO 3104/ ASTM D445	mm <sup>2</sup> /s	54	54	54
Rust Test (distilled water)	ASTM D1743	Rating	Pass	Pass	Pass
Rust Test - EMCOR (distilled water)	DIN 51802	Rating	≤ 0/1	≤ 0/1	≤ 0/1
Copper Corrosion (24 hrs, 100°C / 212°F)	ASTM D4048	Rating	1B	1B	1B
Four Ball Wear test - Wear Scar Diameter	DIN 51350-05E	mm	< 1.0	< 1.0	< 1.0
Four Ball Weld Load test - Weld Point	DIN 51350-04A	N	3600/3800	3600/3800	3600/3800
SRV Friction and Wear test (300 N / 2hr / 50°C)	ASTM D5707	coeff. of friction	0.08	0.08	0.08
Water Resistance	DIN 51807	Rating	1-90	1-90	1-90
Roll Stability Test - Shear Stability	ASTM D1831	0.1 mm	≤ 10	≤ 10	≤ 10
Flow pressure @ -20°C / -4°F	DIN 51805	mbar	350	250	100
Flow pressure @ -35°C / -31°F	DIN 51805	mbar			
Oil separation	DIN 51817	%	≤ 4	≤ 11	
Oil separation	ASTM D1742	%	≤ 3	≤ 3	

Subject to usual manufacturing tolerances.

## Additional Information

Tribol GR 3020/1000 PD should not be mixed with greases using a different thickener.

Application may be made manually with grease guns or automatic dispensing systems designed for the respective NLGI grades.

**This product was previously called Tribol 3020/1000. The name was changed in 2015.**

Tribol™ GR 3020/1000 PD Range

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)