



# CITGO® TRANSGARD® Multi-Vehicle High-Viscosity ATF

## OVERVIEW




- Highest-quality synthetic base stocks combine with a state-of-the-art additive system to provide superior performance in automatic and powershift transmissions.
- Suitable for use in transmissions calling for Ford MERCON®V, Ford MERCON (obsolete), General Motors DEXRON® -IIIH (obsolete), and Allison C-4 type fluids.

## FEATURES & BENEFITS



- Superior oxidation and thermal stability.
- Outstanding anti-wear performance for protection of transmission hardware.
- Excellent cold-temperature flow properties.
- Compatible with a wide range of seal materials to prevent transmission leaks.
- Can be used in most vehicles.
- Provides inventory optimization (multi-vehicle compatible) without the use of ATF supplements.

## APPLICATIONS




Suitable for use where the following specifications are recommended:

- Ford MERCON and MERCON V\* (In California, use TRANSGARD ATF, MERCON V)
- GM DEXRON -II and DEXRON -III
- Allison C-4, TES-295, and TES-389 (not OEM approved)
- BMW LT-71141, ETL-7045E, LA-2634, ETL-8072B
- Nissan/Infiniti Nissan ATF Matic D, Matic J, Matic K and Matic W
- Mitsubishi Diamond J-2, SP-II and SP-III
- Hyundai/KIA SP-II and SP-III
- Toyota/Lexus Type T, T-III and T-IV
- Honda/Acura ATF-Z1 (except in CVTs)
- Mercedes Benz 236.3; .5; .6; .7; .8; .9; .91; .10; and .11; ATF 3403 M-115
- Volkswagen/Audi G052025 (A2); G052055; G052162 (A1, A2); G052990 (A2); G055025 (A2); GUS000162
- ZF TE-ML 11A; 11B
- JASO 1A
- MAN 339A
- Mazda Type T-IV
- Subaru ATF-HP
- Renault Matic D2
- Volvo 1161521; 1161540/1161640; 1273.41

Refer to equipment owner's manual for proper lubricant recommendation.

\*California law prohibits manufacturers of multi-vehicle ATF from recommending products in certain applications where the viscometrics do not match those of the official OEM specification. CITGO therefore does not recommend the use of TRANSGARD Multi-Vehicle High – Viscosity ATF in these applications in California.

**Do not use in vehicles calling for Type F, DEXRON VI, MERCON SP, MERCON LV, Toyota/Lexus WS, and CVTs.**

**PROPERTIES****Typical Properties for CITGO TRANSGARD Multi-Vehicle High-Viscosity ATF:**

<b>Material Code</b>	<b>633131001</b>
Viscosity	
cSt at 40°C	35
cSt at 100°C	6.7
Viscosity Index	153
Specific Gravity @ 60°F	0.851
Pour Point ASTM D97, °F (°C)	-49 (-45)
Brookfield Viscosity @ -40°C, cP	16,280
Appearance	Red

CITGO and TRANSGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. This is not a licensed OEM product. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.