



CITGO TRANSGARD® CVT FLUID

Date 08/15

**DESCRIPTION:** This Full Synthetic, Continuously Variable Transmission Fluid is specifically formulated to prolong and protect transmission life in modern high technology belt and chain-driven CVT transmissions. It helps maintain smooth operation, reduces transmission wear and degrades less over time.

- QUALITIES:**
- Maintains viscosity control over the life of the fluid for smooth shifting and fuel economy.
  - Prevents wear in metal contacts while maintaining the proper frictional values to transfer high levels of torque and prevent shudder.
  - Excellent oxidation control to maximize fluid life and maintain chemical properties.

**APPLICATIONS:** CITGO TRANSGARD CVT Fluid is recommended for use in most foreign and domestic belt and chain-driven CVT transmissions and is suitable for use in the following vehicles where CVT Fluid is recommended:

- |  |  |
|--|--|
| Audi/VW TL52180, G052180, G052516            | Mazda CVTF 3320                          |
| Ford CFT30/WSS-M2C933-A/                     | Mercedes Benz CVT28, MB-Approval 236.20  |
| Motorcraft XT-7-QCFT, MERCON C               | Mini Cooper EZL 799A, ZF CVT V1          |
| SUBARU i-CVTF, Lineartronic CVTF,            | Mitsubishi DiaQueen CVTF-J1              |
| K0425Y0710, CV-30                            | Nissan NS-1, NS-2                        |
| BMW 8322 0 136 376, 8322 0 429 154, EZL 799A | Punch EZL 799A                           |
| Daihatsu Amix CVTF-DC                        | Shell Green 1V                           |
| Dodge/Jeep NS-2, CVTF+4, Mopar CVT 4         | Subaru e-CVTF                            |
| Ford CVT23                                   | Suzuki CVTF 3320, TC, NS-2, CVTF Green 1 |
| GM/Saturn DEX-CVT                            | Toyota Lexus TC                          |
| Honda HMMF, HCF-2                            |  |
| Hyundai/Kia SP-CVT1                          |  |

NOT for E-CVT or Non-CVT transmissions. Consult owner’s manual for fluid recommendations.

**TYPICAL PROPERTIES:**

**CITGO TRANSGARD® CVT FLUID**

Material Code	633134001
Gravity, ASTM D 287, °API	34.5
Density, Pounds Per Gallon	7.1
Flash Point, P.M. D 93, °C	190
Pour Point, ASTM D 97, °F (°C)	-40
Viscosity, 40°C, cSt, D 445	34.5
100°C, cSt, D 445	7.3
Index, D 2270	185
Brookfield Viscosity @ -40°C	10,000
Color	Red

CITGO and TRANSGARD are registered trademarks of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.