

CLARION® FM Spray Grease



OVERVIEW




- An NSF H1 grease packaged with propellant in an aerosol container.
- Provides a convenient means of application for incidental contact grease lubrication applications.

FEATURES & BENEFITS




- Excellent resistance to water washout.
- Antiwear and extreme pressure (EP) protection.
- Pressure separation resistance.
- Excellent rust and corrosion protection.
- Very good compatibility with common food grade greases.
- Meet the requirements of U.S. FDA regulation 21 CFR 178.3570 for incidental food contact.
- NSF H1 registered for use in food processing plants under the jurisdiction of the USDA.

APPLICATIONS



- Recommended for use as a general lubricant and rust preventative grease for food processing machinery.
- Trolley chains (**DO NOT use as an oven chain lubricant**), casters, hinges and sliding mechanisms.
- DANGER: Extremely flammable aerosol. Refer to SDS for proper transport, storage, and handling. Always check with local jurisdictions for warehouse requirements.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES**Typical Properties for CLARION® FM Spray Grease:**

Material and Package Code	633594009190
Propellant	Propane and Butane
Flash Point, ASTM D92, °C (°F)	188 (370)
Spray Pattern	Fine Stream
Texture	Medium Oil Film
Oil Component	
Specific Gravity, ASTM D	0.76
Viscosity, cSt at 40°C	150
cSt at 100°C	16.5
Viscosity Index	94
NSF Registered	H1
(Registration Number)	152455
Meets FDA 21 CFR 178.3570	

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice. CLARION® is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.