

DESCRIPTION

With Jet-Lube® Puncture Seal HD, small punctures and bead leaks are a thing of the past. When a puncture or bead leak occurs, microscopic, nontoxic polymer strands suspended in a liquid solution race to the air leak, adhering to the sides of the opening and builds a long-lasting solid plug, impervious to water, mud and snow. However, Jet-Lube Puncture Seal HD stays in a liquid form and is distributed evenly over the entire inside surface of the tire.

Jet-Lube Puncture Seal HD lubricates to help prevent the rusting of tires and wheels. All too often, tire damage occurs when the rim welds itself to the tire due to rust and heat. With Jet-Lube Puncture Seal HD, this problem is virtually eliminated, which makes tire removal quick and easy.

Jet-Lube Puncture Seal HD is safe and easy to use. It contains no harsh chemicals and safely washes off skin and out of clothing. Jet-Lube Puncture Seal HD is specially designed for use in tires found on equipment used in mines, quarries, construction, and all types of off-road applications.

BENEFITS

- REDUCES COSTLY DOWNTIME.
- MAKES TIRE BREAKDOWN QUICK AND EASY.
- PREVENTS RUST AND CORROSION DAMAGE TO WHEELS AND RIMS.
- INCREASES TIRE LIFE.
- EFFECTIVE IN ALL CLIMATES (contains an anti-freeze).
- LUBRICATES TO PREVENT TIRES "WELDING" TO RIM.

APPLICATIONS

Caution: Jet-Lube Puncture Seal HD Tire Lube and Seal is designed to be used in low-speed off-road tires and non-steering trailer tires. Do not use in automotive and aviation tires or tires on the steering axle of highway vehicles. Jet-Lube Puncture Seal HD will freeze at 0°F (-18°C) but will soften quickly as the tires warm up during travel.

Tractor and Implement Tires		Industrial Tires		Off-Road Tires		Forklift/Loader Mine Equipment	
Size	Pints Per Tire	Size	Pints Per Tire	Size	Pints Per Tire	Size	Pints Per Tire
7.50-10	2	3.40/3.00-5	1	7.50-10	2	2.80/2.50-4	1
9.00-10	3	11.00/4.00-5	1	9.00-10	3	4.00-4	1
4.00-15	1	6.90/6.00-6	1	7.50-15	3	4.10/3.50-4	1
5.00-15	2	12.00/11.00-6	3	10.00-15	4	3.50/-4	1
5.50-16	2	15.00/6.00-6	2	11.00-16	5	5.30/4.50-6	1
6.50-16	3	16.00/11.50-6	3	7.50-20	4	14/8-6	1
8.00-16	4	4.80/4.00-7	1	9.00-20	4	4.00-8	1
9.00-16	4	5.30/4.50-7	1	10.00-20	6	4.80/4.00-8	1
7.50-25	4	6.50-10	2	11.00-20	7	5.00-8	1
10.00-24	6	9.00-10	3	14.00-20	10	5.70/5.00-8	1
13.00-24	9	15.00-10	6	11.00-24	8	17/16-8	1
14.90/13.00-24	10	4.00-12	1	13.00-24	9	18/7-8	1
16.90/14.00-24	12	7.00-12	2	14.00-24	11	5.00-9	1
12.40/11.00-26	8	23.00/8.50-12	3	15.00-25	13	6.90-9	2
13.60/12.00-26	9	26.00/12.00-12	5	18.00-25	15	GOLF CARTS	
11.00-28	8	4.00-15	1	20.50-25	16	6.50-5	1
12.30/11.00-28	9	7.50-15	3	24.00-25	24	7.00-6	1
23.10/18.00-30	15	8.25-15	4	18.00-26	16	8.00-6	1
9.00-32	7	27.00/8.50-15	3	26.50-29	26	16/11.50-6	1
28.10-32	7	44.00/41.00-16	40	30.00-33	32	018/8.50-8	1
30.00-33	32	48.00/20.00-16	16	30.00-40	36	For tire sizes not listed, please call Whitmore's Technical Service Department at 1-800-699-6318	
4.00-36	3	4.00-19	2	21.00-49	25		
11.00-36	9	48.00/25.00-20	19				
12.30-11.00-36	9	66.00/43.00-25	50				
13.6/12-36	12	67.00/34.00-25	34				
12.00-36	10						
12.40/11.00-38	10						
30.00-40	47						
36.00-41	47						
30.00-41	36						

For package types and part numbers

www.jetlube.com/resources/product-index/

Limited Warranty

www.jetlube.com/assets/documents/Jet-Lube_Warranty.pdf

www.jetlube.com

Made in the USA in an ISO 9001:2015 and ISO 14001:2015 Facility