

TECHNICAL DATA SHEET



SAE 5W-20

**PRODUCT # 10516, 10517, 10518, 10642,
18001, 20832**

API SN PLUS/SN/SM, ILSAC GF-5, ACEA A1-12, A5-12

TEST

ASTM

TYPICAL

API Gravity	D-1298	32.2
Specific Gravity @ 60°F	D-1298	.864
Density @ 60°F LBS/US Gal	D-1298	7.205
Viscosity @ 40°C	D-445	47.9
Viscosity @ 100°C	D-445	8
Viscosity Index	D-2270	149
Color		Clear Brown
Flash Point, COC °F	D-92	440

Lucas SAE 5W-20 is a formulation of high quality base stocks and an exclusive high performance additive package. It's the ideal on track/off track lubricant that ensures minimum drag, maximum protection from wear, maximum fuel mileage and easier cold weather starting.

Lucas SAE 5W-20 is the perfect lubricant for the high temperatures of turbo charged engines. It blends with other motor oils, synthetic or petroleum. Expect more miles/kilometers between overhauls and lower oil temperatures.

Lucas SAE 5W-20 has been used extensively and proven excellent for kart engines. It far outlasts conventional oils.

Exceeds American AND European OEM specifications. Exceeds performance levels of API SN PLUS/SN/SM, ILSAC GF-5, ACEA A1-12, A5-12