

## TECHNICAL DATA SHEET



# M8 MARINE GEAR OIL SYNTHETIC SAE 75W-90

PRODUCT #10652, 10664, 10818

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>26.8</b>
<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>.8939</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.443</b>
<b>Viscosity @ 40°C cSt</b>	<b>D-445</b>	<b>142.0</b>
<b>Viscosity @ 100°C cSt</b>	<b>D-445</b>	<b>18.4</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>390</b>
<b>Color</b>		<b>Blue</b>
<b>Viscosity Index</b>		<b>145</b>
<b>Pour Point, °F (°C)</b>	<b>D-97</b>	<b>-38 (-39)</b>
<b>FZG</b>		<b>12 Stage PASS</b>
<b>Brookfield Viscosity @ -40°C</b>	<b>D-2983</b>	<b>80,000 CPS</b>

## Exceeds All API GL Classifications

**API MT-1, API GL-5, MIL-PRF-2105E, MACK GO-G, PG-2 Limited Slip**

**Lucas M8 Synthetic SAE 75W-90 Marine Gear Oil is a pure-synthetic, non-foaming, super slick, long lasting lubricant designed especially for marine applications.**

**Contains a special additive package that cushions gears and resists “squeezing out” under extreme pressure situations where other gear lubricants just don’t hold up. Improved corrosion resistance and water demulsibility over automotive gear oils.**

**We have improved the high speed shock load and significantly improved anti-wear performance which provides the ultimate protection to the gear components.**

**Specially designed to stand up to high temperatures without losing its lubricity.**

**Excellent for use in stern drives, v-drives, gear boxes, wheel bearings, lower end units and superchargers.**