



Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 12/22/2020

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
Product name : Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil
Product code : 11246,11247, 11248, 11249, 11250, 18065

1.2. Recommended use and restrictions on use

Recommended use : Lubricant
Restrictions on use : No additional information available

1.3. Supplier

Lucas Oil Products, Inc
302 North Sheridan Street
Corona, California 92878 - USA
T (951) 270-0154 - F (951) 270-1902
www.LucasOil.com

1.4. Emergency telephone number

:ChemTel
Emergency number 1-800-255-3924 (USA, Canada, Puerto Rico, US V.I.)
+1-813-248-0585 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS-US labelling

No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS-US classification |
|--|----------------------|-----------|---|
| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) | (CAS No) 64742-54-7 | 55 – 85 | Not classified |
| Zinc alkyl dithiophosphate | (CAS No) 113706-15-3 | 0.5 – 1.5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Gently wash with plenty of soap and water.
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Get medical advice/attention.

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/injuries after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water spray.
Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Specific hazards arising from the chemical

Fire hazard : Burning produces irritating, toxic and noxious fumes.
Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition.
Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.
Emergency procedures : Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.
Other information : Spilled material may present a slipping hazard.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid any leak and work in fully closed specially engineered systems.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in original container.
Incompatible products : Strong acids. Strong bases. Strong oxidizers.
Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) | | |
|---|---------------------------------|----------------------|
| ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ |
| ACGIH | ACGIH STEL (mg/m ³) | 10 mg/m ³ |

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | | |
|---|-------------------------------------|---------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) | | |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 5 mg/m ³ |
| Zinc alkyl dithiophosphate (113706-15-3) | | |
| Not applicable | | |

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid splashing. Ensure good ventilation of the work station.
Environmental exposure controls : Prevent leakage or spillage. Prevent contaminated water run-off.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : amber
Odour : petroleum
Odour threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : ≥ 215.5 °C
Relative evaporation rate (butylacetate=1) : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 0.89 g/ml
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity, kinematic : 118 cSt @ 40 °C
Viscosity, dynamic : No data available
Explosive limits : No data available
Explosive properties : No data available
Oxidising properties : No data available

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Hydrocarbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

| | |
|----------------------------|----------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat (mg/l) | > 5.53 mg/l/4h |

Zinc alkyl dithiophosphate (113706-15-3)

| | |
|--------------------|---------------------------|
| LD50 oral rat | 2600 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |
| ATE US (oral) | 2600.000 mg/kg bodyweight |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

(Based on available data, the classification criteria are not met. Component. Not expected to be an irritant)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

| | |
|----------------|--------------|
| EC50 Daphnia 1 | > 10000 mg/l |
|----------------|--------------|

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|-----------------------------|
| Zinc alkyl dithiophosphate (113706-15-3) | |
| LC50 fish 1 | 4.5 mg/l 96 h Rainbow trout |

12.2. Persistence and degradability

| | |
|---|---|
| Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil | |
| Persistence and degradability | May cause long-term adverse effects in the environment. |

| | |
|---|----------------------------|
| Zinc alkyl dithiophosphate (113706-15-3) | |
| Persistence and degradability | Not readily biodegradable. |

12.3. Bioaccumulative potential

| | |
|---|------------------|
| Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil | |
| Bioaccumulative potential | Not established. |

| | |
|---|-----|
| Zinc alkyl dithiophosphate (113706-15-3) | |
| Log Pow | 0.9 |

12.4. Mobility in soil

| | |
|---|------------------|
| Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil | |
| Ecology - soil | Not established. |

| | |
|---|---|
| Zinc alkyl dithiophosphate (113706-15-3) | |
| Ecology - soil | Absorbs to soil particles and will not be mobile. |

12.5. Other adverse effects

Other information : No additional information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

| | |
|---|--|
| Zinc alkyl dithiophosphate (113706-15-3) | |
| EPA TSCA Regulatory Flag | P - P - indicates a commenced PMN substance. |

15.2. International regulations

CANADA

| | |
|---|--|
| Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7) | |
| Listed on the Canadian DSL (Domestic Substances List) inventory. | |

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Zinc alkyl dithiophosphate (113706-15-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Zinc alkyl dithiophosphate (113706-15-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on Taiwan National Chemical Inventory

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on the AICS (Australian Inventory of Chemical Substances)

Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

Data sources

: ACGIH (American Conference of Government Industrial Hygienists).
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Kristen Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information

: None.

Full text of H-statements:

| | |
|------|---------------------------|
| H315 | Causes skin irritation |
| H318 | Causes serious eye damage |

Abbreviations and acronyms:


| | |
|--|---|
| | ATE: Acute Toxicity Estimate |
| | CAS (Chemical Abstracts Service) number |
| | EC50: Environmental Concentration associated with a response by 50% of the test population. |
| | GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). |
| | LD50: Lethal Dose for 50% of the test population |
| | OSHA: Occupational Safety & Health Administration |
| | TSCA: Toxic Substances Control Act |
| | TWA: Time Weighted Average |
| | STEL: Short Term Exposure Limits |

Lucas Magnum SAE 15W-40 Synthetic API CK-4 H-D Motor Oil

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--------------------|--|
| NFPA health hazard | : 1 - Materials that, under emergency conditions, can cause significant irritation. |
| NFPA fire hazard | : 1 - Materials that must be preheated before ignition can occur. |
| NFPA reactivity | : 0 - Normally stable, even under fire exposure conditions, and not reactive with water. |



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product