

TECHNICAL DATA SHEET



SAE 5W-30

**PRODUCT # 10474, 10475, 10477, 10479,
10482, 18010, 20474, 20475**

API SN PLUS/SN/SM, ILSAC GF-5, ACEA A1-12, A5-12

TEST

ASTM

TYPICAL

API Gravity	D-1298	32.3
Specific Gravity @ 60°F	D-1298	.863
Density @ 60°F LBS/US Gal	D-1298	7.15
Viscosity @ 40°C cSt	D-445	60.9
Viscosity @ 100°C cSt	D-445	11.0
Viscosity Index	D-2270	152
Color		Light Brown
Flash Point, COC °F	D-92	460
Pour Point, °C	D-97	-36
CCS @ -30°C, CPS	D-5293	6,600 Max
MRV TP-1 @ -35°C, CPS	D-4684	60,000 Max
P, Wt %	ICP	0.08 Max
Z, Wt %	ICP	0.08 Typ

Lucas SAE 5W-30 is a formulation of high quality base stocks and an exclusive high performance additive package. It's an ideal on track/off track lubricant that ensures minimum drag for maximum fuel mileage, and easy cold weather starting. The user can expect maximum protection from wear even with extended drain intervals.

The exclusive additive package in Lucas SAE 5W-30 ensures extra protection and longer oil life in turbo charged engines. The user can expect more miles/kilometers between overhauls and lower oil temperatures.

Designed for use in gasoline engines only.

Exceeds American and European OEM specifications. Exceeds performance levels of API SN PLUS/SN/SM, ILSAC GF-5, ACEA A1-12, A5-12