

## TECHNICAL DATA SHEET



# PRIMARY CHAINCASE OIL

PRODUCT # 10790

### TEST

### ASTM

### TYPICAL

<b>API Gravity</b>	<b>D-1298</b>	<b>33.03</b>
<b>Specific Gravity</b>	<b>D-1298</b>	<b>0.860</b>
<b>Density @ 60°F LBS/Gal</b>	<b>D-1298</b>	<b>7.16</b>
<b>Viscosity @ 40°C, cSt</b>	<b>D-445</b>	<b>99</b>
<b>Viscosity @ 100°C, cSt</b>	<b>D-445</b>	<b>14.4</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>150</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>420</b>
<b>Color</b>		<b>Amber</b>
<b>CCS @ -25°C, CPS</b>	<b>D-5293</b>	<b>7,000 Max</b>
<b>MRV @ -30°C, CPS</b>	<b>D-4684</b>	<b>60,000 Max</b>

**Lucas Primary Chaincase Oil is specifically designed as a coolant for clutches. It is a blend of the highest quality base oils and unique Lucas additive package that carry away heat from the clutch and friction plates, and helps extend the life of the clutches. It is designed for use in heavy duty and high performance applications and meets or exceeds OEM requirements. It is designed to quiet the chains and improve performance.**