

PRODUCT DATA SHEET



Maralube Bronze GP

Maralube Bronze GP is an NGLI #2, Lithium Soap Grease designed for high-end performance in a variety of environments. This grease uses Lithium 12-HSA Polymer Technology which reduces oil separation and holds the product in place. It offers outstanding water resistance and protects against rust and corrosion. Maralube Bronze is well-positioned to take on agricultural, industrial, and marine applications.

Features

- **Lithium 12-HSA Polymer Technology**
Reduces oil separation and holds product in place
- **Combats Rust & Corrosion**
Fights rust & corrosion, even in water-ingress conditions

Applications

- Agricultural
- Industrial
- Marine

Technical Data

NLGI Grade	Method	2
Product Numbers	1671 (120 # keg), 1672 (35# pail), 1673 (40/14 oz)	
Penetration, mm/10 Worked 60 Strokes	ASTM D217	265-295
Dropping Point, °F (°C)	ASTM D566 or D2265	370 (188)
Thickener Type		Lithium 12-HSA
Color	Visual	Amber
Base Oil Viscosity, Kinematic cSt @ 40°C	D445	ISO 150
Oxidation Stability, lb Loss/100 hours	D942	5
Bearing Rust Protection, Rating	ASTM D1743	Pass
Water Spray-off, %	ASTM D4049	28

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Marathon Petroleum Corporation believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.