



## Mobilube HD Plus 80W-90, 85W-140

Mobil Commercial Vehicle Lube , United States

Extra High Performance Commercial Gear Lubricants

### Product Description

Mobilube HD Plus 80W-90 and 85W-140 are extra high performance commercial gear lubricants formulated from select base oils and an advanced additive system. These lubricants are engineered for performance in heavy-duty commercial transmissions, axles, and final drives where extreme pressures and shock loading are expected. They provide excellent chemical and thermal stability at elevated bulk oil temperatures, good performance at low temperatures, and have demonstrated good rust protection resulting from water contamination and wet conditions. They are recommended by ExxonMobil for applications where API GL-5 and MT-1 service is required. Mobilube HD Plus 80W-90 and 85W-140 share common formulations with Esso Gear Oil GX 80W-90 and 85W-140.

### Features and Benefits

Today's heavy equipment applications place higher performance demands on drive train lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant. Mobilube HD Plus gear lubricants are engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Excellent thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits and longer seal life
Good protection against low speed/high torque wear and against high speed scoring	Increased load carrying capability and reduced operating costs
Excellent rust, staining, and corrosion protection	Reduced wear and longer component life
Effective low temperature lubrication	Reduced wear and ease of start-up
Wide multipurpose capability	Reduced number of gear lubricants to simplify inventory and minimize misapplication
Good resistance to foaming	Maintains film strength for effective lubrication
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

### Applications

#### Recommended by ExxonMobil for use in:

- Heavy-duty manual transmissions, axles, and final drives requiring API GL-5 and MT-1 level performance
- On-highway light and heavy-duty trucks, busses, vans, and cars
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Other heavy-duty industrial and automotive applications involving hypoid and other gears operating under conditions where high speed/shock load, high speed/low torque, and/or low speed/high torque conditions prevail
- Initial fill, top-off, and refill of enclosed commercial gearing in manual or semiautomatic transmissions where gear lubricants are recommended including drive axles and final drives
- Not recommended for applications requiring API GL-4 Level performance
- Not intended for transmissions for which engine oil or automatic transmission fluids are recommended

### Specifications and Approvals

Mobilube HD Plus Gear Oil meets or exceeds the requirements of the following industry specifications:	80W-90	85W-140
API GL-5	X	X
API MT-1	X	X
SCANIA STO-1:0	X	X

Mobilube HD Plus Gear Oil is of the following quality level, but not approved:	80W-90	85W-140
MIL-PRF-2105E	X	X

## Typical Properties

Mobilube HD Plus		
SAE Grade	80W-90	85W-140
Viscosity, ASTM D 445		
cSt @ 40°C	139	333
cSt @ 100°C	14.5	25.4
Viscosity Index, ASTM D 2270	103	99
Pour Point, °C, ASTM D 97	-27	-18
Flash Point, °C, ASTM D 92	210	230
Density @ 15°C kg/l, ASTM D 4052	0.895	0.903

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Mobilube HD Plus are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

### Exxon Mobil Corporation

22777 Springwoods Village Parkway

Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved