Mobil™ ATF+4

Mobil Passenger Vehicle Lube , United States

Semi-Synthetic Automatic Transmission Fluid

Product Description

Mobil ATF+4 is specially formulated to ensure optimal performance in Chrysler automatic transmissions. Its unique additive package provides the proper frictional properties, excellent low-temperature fluidity and dependable wear protection required in applications where a Chrysler MS-9602 type fluid is recommended.

Features and Benefits

The outstanding performance features of Mobil ATF+4 offer the following advantages in Chrysler applications:

- Excellent flow properties at low start-up temperatures and high operating temperatures
- Improved shift performance and vehicle driveability/improved shudder performance in Chrysler vehicles
- Good viscosity stability
- Excellent oxidation stability, less fluid breakdown in high-temperature service
- Dependable protection against rust and corrosion
- Provides more assured wear protection for maximum transmission/transaxle life

Applications

Mobil ATF +4 is recommended by ExxonMobil for use in these applications:

- Automatic transmissions specially formulated for Chrysler vehicles, including Dodge, Plymouth, Eagle and certain Jeeps, that require a fluid meeting ATF+4 specification.
- Mitsubishi and Hyundai applications where an MS-9602 type fluid is specified.
- Services that specify a ATF+, ATF+2 and ATF+3 type fluid, including certain manual transmissions, transfer cases and power steering units (1999 and later).

Mobil ATF+4 is not recommended for vehicles that require Ford Mercon® or General Motors Dexron® type fluids.

Automatic transmissions should be checked for proper fluid levels at regular intervals, and the fluid should be changed at manufacturer-recommended intervals. However, this may vary due to your vehicle's operating conditions. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions, such as heavy traffic, hot weather and trailer pulling.

Specifications and Approvals

This product has the following approvals:
Chrysler MS-9602

Properties and Specifications

Property	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	8800

Property	
Color, Visual	Red
Flash Point, Cleveland Open Cup, °C, ASTM D92	200 (392)
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7.5
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	34.4
Pour Point, °C, ASTM D97	-50 (-58)
Viscosity Index, ASTM D2270	194

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved