



## Mobil™ Multi-Vehicle ATF

Mobil Passenger Vehicle Lube , United States

Automatic Transmission Fluid

### Product Description

Mobil Multi-Vehicle ATF is a premium synthetic blend lubricant formulated for use in a wide variety of North American, European, and Asian vehicles.

### Features and Benefits

Advantages offered by Mobil Multi-Vehicle ATF over transmission fluids of lower quality are:

- Long fluid life and long transmission life
- Exceptional oxidation stability and resistance to chemical deterioration
- Excellent flow properties at low start-up temperatures and high operating temperatures
- Excellent lubricating characteristics for quiet operation, smooth shifting, and excellent wear protection
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening at low starting temperatures
- Dependable protection against rust and corrosion

### Applications

Mobil Multi-Vehicle ATF is a synthetic-blend automatic transmission fluid designed to meet the needs of a broad range of transmission designs and power steering applications. Mobil Multi-Vehicle ATF is not recommended for use in CVT or DCT transmissions.

Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

Recommended by ExxonMobil for use in applications requiring Dexron III, Allison C-4, Ford Mercon and Mercon V.

Mobil Multi-Vehicle ATF is recommended by ExxonMobil as suitable for use in many automatic transmission applications, power steering applications, and vehicle manufacturers including:

- Aisin Warner transmissions: JWS 3309; JWS 3324; AW-1
- Audi/VW: G 052 162; G 052 990; G 055 025; G 055 005; G 055 162; G 055 540
- BMW: 7045E (3 Series); 5 Series; LA 2634; LT 71141

- Chrysler: ATF+2; ATF+3; ATF+4; MOPAR AS68RC; MS-1872; MS-5931; MS-9602; MS-10838
- Ford: Mercon LV; WSS-M2C924-A; WSS-M2C138; WSS-M2C922; WSS-M2C195-A; XL-12 Transfer Case
- GM: Dexron VI; T-IV; ATF Saturn T-IV; AW-1; WS-ATF; GM Auto-Trak II Transfer Case
- Honda: ATF-Z1, ATF DW-1
- Hyundai/Kia: SP- II; SP III; SP-IV M;SP-IV; SP-IV-RR; SPH-IV; NWS 9638; Kia Red-1; JWS 3314; JWS 3317; PSF-3; PSF-4
- Isuzu: SCS
- Mazda: ATF-M III; ATF-MV
- Mitsubishi: SP-II; SP-III; SP-IV; DiaQueen ATF J3; DiaQueen ATF-PA; DiaQueen ATF J2; PS Fluid, Diamond SP III
- Nissan: Matic D; Matic J; Matic K; Matic S; Matic W; PSF-II; Nissan 402
- Subaru: Subaru ATF; Subaru ATF-HP
- Toyota: T; T-I; T-II; T-III; WS (JWS 3324); PSF Type EH
- Voith transmissions: H55.6335; H55.6336

Always check your owner's manual and/or warranty for the required or approved type of ATF, as applicable.

Mobil Multi-Vehicle ATF recommendations are based on a combination of independent field and laboratory testing. ExxonMobil recommends Mobil Multi-Vehicle ATF in a broad range of transmissions. The list of manufacturers and specifications above is just a sample of applications where ExxonMobil supports the use of Mobil Multi-Vehicle ATF. It is important to note that the respective vehicle manufacturers have neither evaluated nor approved Mobil Multi-Vehicle ATF in the applications identified in this document.

#### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
Allison C-4
Ford MERCON
GM DEXRON
GM DEXRON II
GM DEXRON IID
GM DEXRON IIE
GM DEXRON IIIG

**This product is recommended for use in applications requiring:**

GM DEXRON IIIH

JASO 1-A

VOLVO 97340

**This product meets or exceeds the requirements of:**

Ford MERCON V

MAN 339 Typ V1

**Properties and Specifications**

Property	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	34.1
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	7.42
Density @ 15.6 C, g/ml, ASTM D4052	0.851
Color, Visual	Red
Viscosity Index, ASTM D2270	192
Flash Point, Cleveland Open Cup, °C, ASTM D92	200

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

**Exxon Mobil Corporation**

22777 Springwoods Village Parkway  
Spring TX 77389

1-800-ASK MOBIL (275-6624)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved