


# Mystik<sup>®</sup> CalSuPlex<sup>®</sup> Multi-Purpose #2 Grease

Formerly known as CITGO<sup>®</sup> Calsuplex MP Grease

## OVERVIEW



- Specially formulated with a calcium sulfonate thickener in premium base oils.
- Provides excellent performance in a wide variety of automotive, heavy duty, and industrial applications.
- Provides excellent corrosion control for high moisture environments.

## FEATURES & BENEFITS



- Provides superior protection against corrosion in the presence of water.
- Provides excellent extreme pressure (EP) and anti-wear protection under severe conditions.
- Provides outstanding resistance to oxidation.
- Highly resistant to water washout.
- Meets the ASTM D4950 requirements for Wheel Bearing Grease Category GC and Chassis Grease Category LB.



## APPLICATIONS



- Recommended for a wide range of automotive and industrial applications including bearings, ball joints, and bushings.
- Refer to equipment owner's manual for proper lubricant recommendation.

**PROPERTIES****Typical Properties for Mystik CalSuPlex Multi-Purpose #2:**

<b>Material Code</b>	<b>655582002</b>
NLGI Grade	2
Thickener Type	Calcium Sulfonate
Color	Green
Texture	Smooth, Adhesive
Worked Penetration, ASTM D217	265-295
Dropping Point, ASTM D2265, °F(°C)	500 (260)
Rust Prevention, ASTM D1743, Rating	Pass
Water Washout, ASTM D1264, % loss @ 175°F	2
Low Temperature Torque, ASTM D4693, Nm	9.6
High Temperature Life, ASTM D3527, hrs.	120
Four-Ball Wear, ASTM D2266, mm	0.5
Four-Ball Weld, ASTM D2596, kgf	500
Four-Ball Load-Wear Index, ASTM D2596, kgf	60
Base Oil Viscosity @ 40°C, cSt	120
NLGI Classification, ASTM D4950	GC-LB

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.