

Mystik® JT-4® Synthetic 2-Cycle Personal Watercraft Engine Oil

OVERVIEW



- Premium synthetic base oils, combined with a special synthetic additive system designed for personal watercraft engines, provide superior high-temperature oxidation stability, wear protection, and fuel economy.
- Unique tri-blend of synthetic components provides ideal high-temperature performance and quick starts in all temperatures.

FEATURES & BENEFITS



- Provides the best protection against engine wear, rust, and corrosion, ensuring engine cleanliness and promoting longer engine life.
- Superior protection in high temperatures.
- Improves equipment performance and reliability.

APPLICATIONS



- For use in all air-cooled or liquid-cooled 2-cycle (injector or pre-mix) personal watercraft engines including those manufactured by Sea Doo, Kawasaki, Polaris, Yamaha, and other original equipment manufacturers.
- Advanced formula far exceeds personal watercraft engine requirements for API TC and JASO FC quality oil.
- Ideal for engines operating in high temperatures and where performance demands the most from your oil.
- Refer to equipment owner's manual for proper lubricant recommendation.

DO NOT USE IN OUTBOARD MARINE ENGINES!

PROPERTIES**Typical Properties for Mystik JT-4 Synthetic 2-Cycle Personal Watercraft Engine Oil:**

| Material Code | 663076002 |
|--------------------------------------|------------------|
| Gravity, ASTM D237, °API | 32.9 |
| Density, lb/gal | 7.17 |
| Flash Point, PMCC, ASTM D93, °F (°C) | 194 (90) |
| Flash Point, ASTM D92, COC, °F (°C) | 230 (110) |
| Pour Point, ASTM D97, °F (°C) | -54 (-48) |
| Viscosity, ASTM D445 | |
| cSt at 40°C | 54 |
| cSt at 100°C | 9.2 |
| Viscosity Index, ASTM D2270 | 152 |
| Visual Color | Purple |
| Sulfated Ash, ASTM D874, m% | 0.015 |
| TBN, ASTM D2896, mg KOH/g | 4.3 |

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.