

# Mystik<sup>®</sup> JT-4<sup>®</sup> Premium High Performance Lower Unit Gear Lubricant

## OVERVIEW




- Formulated specifically for the marine industry, with the latest generation of a proprietary EP additive system designed to provide maximum protection against wear, rust, corrosion, and deposits.

## FEATURES & BENEFITS



- An improved gear lubricant, specifically designed for boating applications, offering top-level protection, surpassing other marine gear lubricants using GL-4 and GL-5 80W-90 technology.
- Superior EP lubrication and corrosion protection in the presence of moisture (fresh and sea water).
- Improved gear protection for shock load conditions encountered with harsh startup engagement, power reversal, and propeller entanglement.

## APPLICATIONS



- Recommended for use in all outboard and stern drive gear units specifying SAE 90, 80W-90, or 85W-90, including OMC Type 'C.' Includes MerCruiser, OMC Cobra, and Volvo stern drives and Mercury, Evinrude, Johnson, Mariner, Yamaha, Suzuki, and Force outboards.
- Refer to equipment owner's manual for proper lubricant recommendation.

## PROPERTIES



### Typical Properties for Mystik JT-4 Premium High Performance Lower Unit Gear Lubricant:

SAE GRADE	80W-90
Material Code	663090002
Gravity, ASTM D4052, °API	27.2
Density, lb/gal AT 60°F	7.43
Flash Point, ASTM D92, COC, °F (°C)	367 (186)
Viscosity, cSt at 100°C, ASTM D445	16.0
Brookfield Viscosity, -26°C, cP, ASTM D2983	105,600
Pour Point, ASTM D97, °F (°C)	-28 (-33)
Channel Point, °F (°C), Max	-31 (-35)
Color, Visual	Blue
Foram Test, ASTM D892	Pass
Copper Corrosion, 3 hrs at 250°F, ASTM D130	1A

Mystik and JT-4 are registered trademarks protected by federal law. All other registered trademarks or trademarks are the property of their respective owners.