


Mystik® Non-Detergent General Purpose Oils

OVERVIEW




- Designed for use in non-critical applications where a general purpose oil is desired, including low-pressure hydraulic systems such as hydraulic jacks and air compressors requiring a non-detergent type lubricant.

FEATURES & BENEFITS




- Available in SAE 10W, 20W-20, 30 and 40 viscosity grades.

APPLICATIONS



- For use in low-pressure hydraulic systems and compressors where a non-detergent lubricant is required.
- Not recommended for use in gasoline or diesel engines.
- Refer to equipment owner's manual for proper lubricant recommendation.

PROPERTIES



Typical Properties for Mystik Non-Detergent General Purpose Oils:

Material Code	663111002	663112002	663113002	663103002
SAE Grade	10W	20W-20	30	40
ISO Grade (Approx.)	32	68	100	150
Density, lb/gal at 60°F (Approx.)	7.54	7.6	7.65	7.6
Viscosities (Approx.):				
cSt at 100°C	5.0	8.0	11	14.0
cSt at 40°C	29	62	119	154
SUS at 210°F	44	54	—	—
SUS at 100°F	165	340	—	—
Viscosity Index	95	95	95	90
Flash Point, ASTM D92, °F (°C)	380 (193)	395 (202)	425 (218)	430 (221)
Pour Point, ASTM D97, °F (°C)	-25 (-32)	-10 (-23)	-5 (-20)	0 (-18)

Mystik is a registered trademark of CITGO Petroleum Corporation.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.