

Mystik® Turbine Drip Oil

OVERVIEW



- Lubricates dripper lubrication systems for irrigation water well line shaft bearings where a food grade product is **NOT** required.

FEATURES & BENEFITS



- Formulated with highly refined lubricating base oils and a foam suppressant.

APPLICATIONS



NOTE: This lubricant is not recommended for use where a food grade quality lubricant is required. This product should not be used for potable water well pump lubrication. It is the user's responsibility to ensure proper selection of lubricating oil for agricultural irrigation and related systems; refer to applicable regulatory agency requirements.

PROPERTIES



Typical Properties for Mystik Turbine Drip Oil:

Material Code	663435002
SAE Grade	10W
ISO Grade	32
Gravity, °API ASTM D4058	34
Density, lb/gal at 60°F	7.1
Specific Gravity @ 60°F ASTM D1298	0.85
Viscosity, Brookfield @ -25°C, cP ASTM D2893	6400
Viscosity ASTM D445	
cSt at 40°C	32
cSt at 100°C	5.2
SUS at 100°F	150
SUS at 210°F	42.4
Viscosity Index ASTM D2270	108
Flash Point, COC, °F (°C) ASTM D92	380 (193)
Pour Point, °F (°C) ASTM D97	-38 (-39)
Color, ASTM D1500	0.5

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.