

# Mystik® Rock Drill Oil 150

## OVERVIEW



- Formulated to provide excellent extreme pressure (EP) and antiwear performance in heavy duty pneumatic tools.

## FEATURES & BENEFITS




- Excellent EP and antiwear performance.
- Emulsifies for extra lubricity in moist or wet conditions.
- Tackiness reduces splatter and enhances non-drip properties.
- Low pour point enables excellent performance in extremely cold temperatures.
- Provides outstanding rust and corrosion protection.

## APPLICATIONS



- Recommended for rock drills, jackhammers, and other pneumatic tools requiring premium performance lubrication.
- Recommended for industrial and mining equipment working in humid or wet conditions.
- Can be used as a way oil in industrial slideway or non-drip oil applications.
- Refer to equipment owner's manual for proper lubricant recommendation.

**PROPERTIES****Typical Properties for Mystik Rock Drill Oil 150:**

<b>Material Code</b>	<b>663814002</b>
<b>ISO Viscosity Grade</b>	<b>150</b>
SAE Viscosity Grade (Approx.)	40
Gravity, °API ASTM D4052	29.1
Density, lb/gal @ 60°F	7.34
Flash Point, COC, °F (°C) ASTM D92	475 (246)
Pour Point, °F (°C) ASTM D97	-38 (-39)
Viscosity ASTM D445	
cSt at 40°C	146
cSt at 100°C	15.5
SUS at 100°F	764
SUS at 210°F	81.73
Viscosity Index ASTM D2270	115
Color, ASTM D1500	L0.5
Timken OK Load, lbs. ASTM D2782	60
Falex Load, lbs. ASTM D3233A	2100
Four Ball EP Test, Weld, ASTM D2783, kgf	250
Four Ball Wear, ASTM D4172B: 1200 RPM; 40kg; 75°C; 1 hour, Wear Scar, mm	0.42
Rust Test, ASTM D665 A&B	Pass
Copper Corrosion, ASTM D130; 3 hours at 100°C	1b

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners. Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.