


# Mystik® General Purpose Grease

## OVERVIEW




- A multi-purpose grease especially suited for normal temperature and speed conditions, non-critical service applications, and contaminating environments.

## FEATURES & BENEFITS




- Water-resistant.
- Economical.

## APPLICATIONS



- Suited for normal temperatures and speeds.
- Recommended for non-critical applications.
- Recommended for applications requiring frequent re-greasing due to a contaminating environment.
- Refer to equipment owner's manual for proper lubricant recommendation.

## PROPERTIES



### Typical Properties for Mystik General Purpose Grease:

|  |                       |
|--|-----------------------|
| <b>Material Code</b>                               | <b>665150002</b>      |
| NLGI Consistency Number                            | 2                     |
| Thickener Type                                     | Lithium Stearate      |
| Texture  | Smooth, Medium Fiber  |
| Color  | Dark Brown            |
| Worked Penetration, ASTM D217                      | 265-295               |
| Dropping Point, ASTM D566, °F (°C)                 | 320 (160)             |
| Approximate Application Temperature Range, °F (°C) | 0 to 265 (-18 to 129) |

Mystik is a registered trademark of CITGO Petroleum Corporation. All other registered trademarks or trademarks are the property of their respective owners.

Values shown are typical values only and do not constitute a specification. The information contained herein is subject to change without notice.