

# PENNZOIL® SAE 30 MOTOR OIL

## TECHNICAL DATA SHEET



Pennzoil® Motor Oil mono-grade conventional formula with Active Cleansing Technology. Helps prevent dirt and contaminants from turning into performance robbing deposits. Because at Pennzoil® we know, a cleaner engine is better protected and responsive. It meets or exceeds the engine protection required by API SN.

### PERFORMANCE, FEATURES & BENEFITS

Pennzoil® SAE 30 motor oil mono-grade with active cleansing technology:

- Keeps engine clean and responsive
- Provides proven wear protection

### MAIN APPLICATIONS

Pennzoil® Conventional mono-grade SAE 30 is recommended for use in all vehicles requiring the use of SAE 30 viscosity grade engine oils under all driving conditions.

Pennzoil® SAE 30 Motor Oil can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

### TYPICAL PHYSICAL CHARACTERISTICS

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

### SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Exceeds the requirements of the following industry specifications:

- API SN and all previous Categories

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

To find the right Pennzoil® product for your vehicles and equipment, please consult [www.pennzoil.com](http://www.pennzoil.com) to look up the right motor oil recommendation using our oil selector.

Properties		Method	Pennzoil® SAE 30 Motor Oil
Viscosity Grade		SAE J300	30
Service Category			SN
ILSAC			N/A
ACEA			N/A
Density	kg/m <sup>3</sup>	ASTM D4052	879
Flash Point	°C	ASTM D93	232
Pour Point	°C	ASTM D97	-30
Kinematic Viscosity	@40°C cSt	ASTM D445	98
Kinematic Viscosity	@100°C cSt	ASTM D445	11.4
Viscosity Index		ASTM D2270	105
CCS Viscosity			N/A

© SOPUS Products 2020. All rights reserved.

## **PENNZOIL® SAE 30 MOTOR OIL**

<b>Properties</b>	<b>Method</b>	<b>Pennzoil® SAE 30 Motor Oil</b>
<b>MRV Viscosity</b>		N/A

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

### **HEALTH, SAFETY & ENVIRONMENT**

#### **Health and Safety**

Pennzoil® SAE 30 Motor Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

#### **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

#### **ADDITIONAL INFORMATION**

##### **Advice**

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Helpdesk.