

# PENNZOIL® QUICK LUBE CONVENTIONAL SAE 5W-20 MOTOR OIL

TECHNICAL DATA SHEET



Pennzoil® Quick Lube Conventional Motor Oil is formulated with Active Cleansing Agents. It helps prevent dirt and contaminants from turning into performance robbing deposits. Because at Pennzoil® we know, a cleaner engine is better protected and responsive. It meets or exceeds the engine protection required by ILSAC GF-6A.

## PERFORMANCE, FEATURES & BENEFITS

Pennzoil® Motor Oil with active cleansing agents™

- Helps to keep your engine clean
- Provides base wear protection
- Suitable for all cars, SUV, light van and truck gasoline engines; under all driving conditions.

## MAIN APPLICATIONS

Pennzoil® Quick Lube Conventional SAE 5W-20 Motor Oil is recommended for use in all vehicles requiring the use of SAE 5W-20 viscosity grade engine oils under all driving conditions.

Pennzoil® Quick Lube Conventional SAE 5W-20 Motor Oil can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

## TYPICAL PHYSICAL CHARACTERISTICS

Properties	Method	PENNZOIL® QUICK LUBE CONVENTIONAL SAE 5W-20 MOTOR OIL
Viscosity Grade	SAE J300	5W-20
Service Category		SP-RC
ILSAC		GF-6A
ACEA		N/A
Density	15°C kg/m <sup>3</sup>	ASTM D4052 855.5

## SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Meets or exceeds the following OEM requirements:

- Chrysler MS-6395
- Ford WSS-M2C945-A
- Ford WSS-M2C945-B1
- General Motors GM 6094M

Exceeds the requirements of the following industry specifications:

- API SP-Resource Conserving and all previous Categories
- API SP
- ILSAC GF-6A and all previous ILSAC Standards

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

To find the right Pennzoil® product for your vehicles and equipment, please consult [www.pennzoil.com](http://www.pennzoil.com) to look up the right motor oil recommendation using our oil selector.

© SOPUS Products 2020. All rights reserved.

## PENNZOIL® QUICK LUBE CONVENTIONAL SAE 5W-20 MOTOR OIL

Properties			Method	PENNZOIL® QUICK LUBE CONVENTIONAL SAE 5W-20 MOTOR OIL
Flash Point		°C	ASTM D93	229
Pour Point		°C	ASTM D97	-42
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.6
Kinematic Viscosity	@40°C	cSt	ASTM D445	49.0
Viscosity Index			ASTM D2270	155
CCS Viscosity	@-30°C	cP	ASTM D5293	5 170
MRV Viscosity	@-35°C	cP	ASTM D4684	15 600

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

### HEALTH, SAFETY & ENVIRONMENT

#### Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

#### Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

### ADDITIONAL INFORMATION

#### Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or local technical helpdesk.