

PENNZOIL® FULL SYNTHETIC HIGH MILEAGE MOTOR OIL SAE 0W-20 *Full Synthetic Motor Oil*

TECHNICAL DATA SHEET



Pennzoil® Full Synthetic High Mileage motor oil is formulated to provide 40% better performance than conventional high mileage motor oil*. It also allows for fewer oil changes compared to conventional motor oil. So, if your car already requires full synthetic or if you're looking to upgrade from a conventional or synthetic blend high mileage fluids, Pennzoil® Full Synthetic High Mileage is the right choice for you. PENNZOIL® Full Synthetic High Mileage motor oil is formulated for modern turbocharged engines. PENNZOIL® utilizes the advances of synthetic technology to provide enhanced wear protection in high and low temperatures and improved cleanliness over synthetic blend motor oils. It meets or exceeds the engine protection required by ILSAC GF-6.

* Compared to Pennzoil® Conventional High Mileage Motor Oil

PERFORMANCE, FEATURES & BENEFITS

- 40% better performance than conventional motor oil.¹
- Fewer oil changes compared to conventional motor oil.
- Enhanced wear protection in high and low temperatures.
- Helps prevent sludge and deposit build up.
- Excellent resistance to oil breakdown in severe environments
- Suitable for use in new and old engines.

¹ Compared to Pennzoil® Conventional High Mileage motor oil

MAIN APPLICATIONS

PENNZOIL® Full Synthetic High Mileage SAE 0W-20 motor oil is recommended for use in all vehicles requiring the use of SAE 0W-20 viscosity grade engine oils under all driving conditions. SAE 0W-20 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology for maximum fuel economy and performance.

It is also suitable for use and offers the same protection as SAE 5W-20. It can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions. SAE 0W-20 may not be suitable for use in older engines, so always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

- Chrysler MS 6395
- Ford WSS-M2C962-A1

Exceeds the requirements of the following industry specifications:

- API SP -Resource Conserving and all previous Categories
- ILSAC GF-6/A

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

© SOPUS Products 2022. All rights reserved.

PENNZOIL® FULL SYNTHETIC HIGH MILEAGE MOTOR OIL SAE 0W-20

Full Synthetic Motor Oil

TYPICAL PHYSICAL CHARACTERISTICS

Properties	Method	Pennzoil® Full Synthetic High Mileage Motor Oil SAE 0W-20		
Viscosity Grade	SAE J300	0W-20		
Service Category		SP		
ILSAC		GF-6A		
Density	kg/m ³	ASTM D4052	832.2	
Flash Point	°C	ASTM D93	241	
Pour Point	°C	ASTM D97	-51	
Kinematic Viscosity	@ 40°C	cSt	ASTM D445	45.8
Kinematic Viscosity	@ 100°C	cSt	ASTM D445	8.7
Viscosity Index		ASTM D2270	171	
CCS Viscosity	@-35°C	cP	ASTM D5293	4 339
MRV Viscosity	@-40°C	cP	ASTM D4684	13 400

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Shell Lubricants distributor representative or Shell Technical Helpdesk.

To find the right Pennzoil® product for your vehicles and equipment, please consult www.pennzoil.com to look-up the right motor oil recommendation using our oil selector