



Previous Name: Shell Alvania Grease RL 2

Shell Gadus S2 V100 2

- *Reliable Protection*
- *Multi-purpose*
- *Lithium*

High Performance Multipurpose Grease

Shell Gadus S2 V100 2 is a general purpose grease based on a new lithium hydroxystearate soap thickener fortified with anti-oxidant, anti-wear and anti-rust additives.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Reliable high temperature performance**

Very good performance up to +130°C, resulting in longer bearing life.

- **Good oxidation and mechanical stability**

Resists the formation of deposits caused by oxidation at high operating temperatures. Shell Gadus S2 V100 greases are extremely stable under vibrations and give NO LEAKAGE even in repeated shock-loaded bearings.

- **Good corrosion resistance characteristics**

Effective protection in hostile environments.

- **Long storage life**

Does not alter in consistency during prolonged storage.

- Rolling element and plain grease lubricated bearings
- Electric motor bearings
- Sealed-for-life bearings
- Water pump bearings

May be used under a wide range of operating conditions offering very significant advantages over conventional lithium greases at high temperature or in the presence of water.

- A medium consistency grease designed, mainly, for general industrial lubrication. Ideal for centralized lubrication systems operating at normal temperatures.

Specifications, Approvals & Recommendations

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Main Applications



Typical Physical Characteristics

Properties			Method	Shell Gadus S2 V100 2
NLGI Consistency				2
Soap Type				Lithium hydroxystearate
Base Oil (Type)				Mineral
Kinematic Viscosity	@40°C	cSt	IP 71 / ASTM D445	100
Kinematic Viscosity	@100°C	cSt	IP 71 / ASTM D445	11
Cone Penetration, Worked	@25°C	0.1mm	IP 50 / ASTM D217	265-295
Dropping Point		°C	IP 396 / ASTM D2265	180

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

- **Health and Safety**

Shell Gadus S2 V100 Grease is unlikely to present any significant health or safety hazard when properly used in the

recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.Shell.com/>

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

- **Re-greasing Intervals**

For bearings operating near their maximum recommended temperatures, re-greasing intervals should be reviewed.

- **Advice**

Product recommendations for applications and specifications not covered here may be obtained from your Shell representative.