



Shell EcoSafe Revive-L

Readily Biodegradable Fluid Treatment

Shell EcoSafe Revive-L is a base-oil modifier that can be incorporated into a commercial hydrocarbon based gear oil to significantly reduce the issues associated with varnish formation and product instability . Due to its PAG based technology, Shell EcoSafe Revive-L significantly improves lubricity of the fluid.

DESIGNED TO MEET CHALLENGES

Typical Physical Characteristics

Properties			Method	Shell EcoSafe Revive-L
ISO Viscosity Grade				46
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	43.9
Density	@15°C	kg/m ³	ASTM D4052	1 009
Flash Point		°C	ASTM D92	174
Pour Point		°C	ASTM D97	-30
TAN		mg KOH/g	ASTM D664	0.16

These characteristics are typical of current production, variations in these characteristics in future production may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

- Advice on applications not covered here may be obtained from your Shell Representative.