



Formerly Known As: Versa E00-38

Shell Air Compressor Oil S2 R 38

Special Purpose Compressor Lubricant

Shell Air Compressor Oil S2 R 38 is a lubricant manufactured from a special high pressure hydrotreated base oil and a combination of zinc free additives that make it ideal for rotary screw air compressor applications.

DESIGNED TO MEET CHALLENGES

Typical Physical Characteristics

Properties			Method	Shell Air Compressor Oil S2 R 38
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	40.4
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	6.8
Viscosity Index				125
Density	@15°C	kg/m ³	ASTM D4052	847
TAN		mg KOH/g	ASTM D664	0.4

These characteristics are typical of current production, variations in these characteristics in future production may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell Representative.