



Formerly Known As: **Shell Naturelle HF-E 32**

# Shell Naturelle S2 Hydraulic Fluid 32

*Environmentally Acceptable, Synthetic Hydraulic Fluid*

- EU Ecolabel
- Versatile Applications
- US EPA VGP Compliant



Shell Naturelle S2 Hydraulic Fluid is an advanced hydraulic fluid for use in hydraulic and power transmission systems. Readily biodegradable with low ecotoxicity, Shell Naturelle S2 Hydraulic Fluid is particularly suited for use in environmentally sensitive areas. Fully synthetic esters, blended with ashless additives, provide Shell Naturelle S2 Hydraulic Fluid with an excellent blend of lubrication performance and environmental acceptability.

## DESIGNED TO MEET CHALLENGES

### Performance, Features & Benefits

- **Excellent wear protection**

Advanced ashless (zinc and metal free) anti-wear additives provide protection over a wide range of conditions – proven protection in tough industry standard tests such as the Eaton Vickers 35VQ25 vane pump and Komatsu HPV35+35 high pressure piston pump.

- **Maintaining system efficiency**

Excellent viscosity/temperature characteristics can minimize the changes of viscosity with variation in operation temperature, giving true 'multigrade' characteristics. Outstanding cleanliness and filterability, coupled with excellent water separation, air release and antifoam characteristics, all help contribute to maintaining or enhancing the efficiency of hydraulic systems

- **Readily biodegradable**

Shell Naturelle S2 Hydraulic Fluid is biodegradable by exhibiting over 60% biodegradation after 28 days in the OECD 301 B carbon dioxide evolution test.

- **Low toxicity towards the environment**

Shell Naturelle S2 Hydraulic Fluid is classified as 'not harmful' to bacteria, algae, freshwater invertebrates, and fish when tested as water-accommodated fractions (WAFs) according to OECD test guidelines.

- **Very high renewables content**

Shell Naturelle S2 Hydraulic Fluid has mean biobased content of 82% (ASTM D 6866).

### Main Applications



- **Environmentally sensitive areas**

Shell Naturelle S2 Hydraulic Fluid is an 'environmentally acceptable' hydraulic fluid (ISO 15380 HEES), with 'reduced harm for water and soil during use' (EU Ecolabel). When compared to conventional mineral oil hydraulic fluids, it will have a reduced environmental impact in the event of a leak or accidental spillage. It is particularly suited for use in environmentally sensitive areas. However, Bulk operating temperatures should not be allowed to exceed 90°C.

### Specifications, Approvals & Recommendations

- Meets USDA Bio-preferred programme
- Meets requirements of EU Ecolabel certificate number NL/027/019
- ISO 15380 HEES
- Swedish standard SS 15 54 34 SP
- Meets requirement of United States Environmental Protection Agency's (EPA) 2013 vessel general permit (VGP)

For a full listing of equipment approvals and recommendations please consult your local Shell Technical Helpdesk, or the OEM Approval website.

## Compatibility & Miscibility

### • Fluid Compatibility

Shell Naturelle S2 Hydraulic Fluid is miscible with mineral oil fluids and most other ester based biodegradable hydraulic fluids. However, in order to ensure that the environmental properties and performance of Shell Naturelle S2 Hydraulic Fluid are maintained, the hydraulic system should be drained and flushed thoroughly when changing fluids. Guidelines on fluid change-over can be found in ISO 15380 Annex A.

### • Seal & Paint Compatibility

Shell Naturelle S2 Hydraulic Fluid is compatible with fluoroelastomers (FPM/FKM) such as Viton.

Other seal materials and system components such as paints may be adversely affected and advice should be sought from the respective manufacturers.

## Typical Physical Characteristics

Properties		Method	Shell Naturelle S2 Hydraulic Fluid 32	
Viscosity grade			32	
ISO Fluid Type		ISO 6743-4	HEES	
Kinematic Viscosity	@-20°C	cSt	ASTM D445	871
Kinematic Viscosity	@40°C	cSt	ISO 3104	32.5
Kinematic Viscosity	@100°C	cSt	ISO 3104	7.22
Viscosity Index			ISO 2909	196
Density	@15°C	kg/m <sup>3</sup>	ISO 12185	918
Flash Point (Cleveland Open Cup)		°C	ISO 2592	246
Pour Point		°C	ISO 3016	-39
Biodegradable		% 28days	OECD 301B	79

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

### • Health and Safety

Shell Naturelle S2 Hydraulic Fluid is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

### • Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

### • Advice

Advice on applications not covered here may be obtained from your Shell representative.