

January 24, 2022

Klüber Lubrication NA LP • 9010 CR 2120, Tyler, Texas 75707 • Phone 903.534.8021 • sales@klsummit.com

Product Data Sheet

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor does it serve as a license to operate any patent. Due to widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suitability. Product typical properties in this publication are current.

SYNTHETIC BLEND OVEN CONVEYOR CHAIN OIL

CO-400 High Temp Chain Oil

Summit CO-400 High Temperature Chain Oil is a unique formulation of special ester base stocks and the latest additive technology. CO-400 has an exceptionally high smoke point and is capable of penetrating and removing carbonaceous deposits and inhibiting the formation of solid buildup. It is effective over a broad temperature range and results in lower power consumption under varying load conditions.

APPLICATIONS:

Summit CO-400 High Temperature Chain Oil is recommended for use in the following applications:

- High Temperature Process Ovens
- Can and Fibre Board Lines
- Extrusion Paint Lines
- Tenter Frames
- Open Bearings and many other Roller Chain Operations requiring a lubricant with excellent heat stability
- Drying Operations
- Glass Fibre Ovens
- Multi-Purpose E.P. Gears

Physical Properties

Characteristics	Typical Performance
ISO Grade	150
Viscosity	
@ 100°F, cSt	154.8
@ 210°F, cSt	19.05
@ 100°F, SUS	717
@ 210°F, SUS	94.48
Viscosity Index	150
Pour Point, °F (°C)	-60 (-51)
Flash Point, °F (°C)	555 (291)
Specific Gravity	0.911
Density, lbs/gal	7.59
NSF Registered	H2

Shelf Life: Product shelf life is 3 years from the date of manufacture, after which the product should be recertified prior to use.