

SHV Series

Synthetic vacuum pumps



Your benefits at a glance

- Excellent water separation
- Provide protection against wear, rust and corrosion

Your requirements - our solution

The Summit SHV Series is formulated from vacuum distilled ultra-pure synthetic hydrocarbon base stock to provide an extremely low vapor pressure vacuum pump lubricant. These non-foaming fluids have excellent water separation and provide protection against wear, rust and corrosion. The SHV Series is an extended life lubricant designed to function in applications subject to severe temperature and environmental conditions.

Application notes

The Summit SHV Series are compatible with commonly used seal and gasket materials in vacuum pump service.

Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	SHV-15	SHV-22	SHV-32	SHV-46
Article number	340159	340160	340161	340162
Demulsifying capacity	40/40/0 (10) (min)	40/40/0 (10) (min)	40/40/0 (10) (min)	40/40/0 (10) (min)
Density	0.814 g/cm ³	0.819 g/cm ³	0.824 g/cm ³	0.829 g/cm ³
Flash point	185 °C	185 °C	185 °C	185 °C
Ignition Point	377 °C	382 °C	387 °C	393 °C
Kinematic viscosity, 100°C	3.5 mm ² /s	4.5 mm ² /s	5.7 mm ² /s	7.3 mm ² /s
Kinematic viscosity, 40°C	15.2 mm ² /s	21.2 mm ² /s	29.9 mm ² /s	43.2 mm ² /s
Viscosity index	113	129	134	133
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree	1 - - corrosion degree
Pour point	-57 °C	-62 °C	-62 °C	-39 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	60 months	60 months	60 months

Characteristics	SHV-68	SHV-100
Article number	340163	340158
Demulsifying capacity	40/40/0 (10) (min)	40/39/0 (15) (min)
Density	0.832 g/cm ³	0.86 g/cm ³
Flash point	185 °C	240 °C

SHV Series

Synthetic vacuum pumps



Characteristics	SHV-68	SHV-100
Ignition Point	396 °C	404 °C
Kinematic viscosity, 100°C	9.6 mm ² /s	12.5 mm ² /s
Kinematic viscosity, 40°C	63.7 mm ² /s	93.0 mm ² /s
Viscosity index	132	130
Copper corrosion	1 - - corrosion degree	1 - - corrosion degree
Pour point	-42 °C	-40 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	60 months	36 months

Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /
9010 County Road 2120, Tyler, TX 75707 /
Phone: +1 800 749 5823 / www.klsummit.com

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.