

# TM Series

Synthetic blend air compressors



## Your benefits at a glance

- Improved rust and oxidation protection versus general or multi-purpose R&O circulation oils
- Reduced lubricant consumption - extended drain intervals and lower vapor pressures reduce lubricant consumption
- Reduced maintenance - SYNTHOLATE reduces carbon and varnish formation thus extending valve life and the time interval overhauls
- Eliminates recompression - SYNTHOLATE keeps the valves clean and eliminates the primary cause of recompression
- Reduced power consumption - elimination of recompression and reduced coefficient of friction result in less power consumption per unit of compression
- Improved safety - higher flash points provide a greater margin of safety in air compression

## Your requirements - our solution

The Summit TM Series is formulated from highly refined hydrocracked base stocks and the unique additive SYNTHOLATE inhibits the formation of varnish and carbon and provides superior thermal and oxidative stability. Utilizing the superior petroleum base stocks fortified with SYNTHOLATE extends the life of the Summit TM Series compared to that of conventional mineral oils.

## Material safety data sheets

Material safety data sheets can be requested via our website <https://www.klsummit.com>. You may also obtain them through your contact person at Summit Lubrication.

Characteristics	TM-20	TM-30	TM-10	TM-40
Article number	340179	340180	340177	340181
Density	0.871 g/cm <sup>3</sup>	0.88 g/cm <sup>3</sup>	0.864 g/cm <sup>3</sup>	0.88 g/cm <sup>3</sup>
Flash point	243 °C	250 °C	227 °C	250 °C
Kinematic viscosity, 100°C	8.5 mm <sup>2</sup> /s	11.2 mm <sup>2</sup> /s	5.4 mm <sup>2</sup> /s	14.7 mm <sup>2</sup> /s
Kinematic viscosity, 40°C	63.9 mm <sup>2</sup> /s	99.2 mm <sup>2</sup> /s	32.1 mm <sup>2</sup> /s	147.7 mm <sup>2</sup> /s
Viscosity index	103	99	102	98
Pour point	-35 °C	-36 °C	-42 °C	-36 °C
Four-ball tester: wear characteristics	0.6 mm	0.6 mm	0.6 mm	0.6 mm
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months	36 months

Characteristics	TM-15
Article number	340178
Density	0.87 g/cm <sup>3</sup>
Flash point	220 °C
Kinematic viscosity, 100°C	6.8 mm <sup>2</sup> /s

# TM Series

Synthetic blend air compressors



Characteristics	TM-15
Kinematic viscosity, 40°C	44.0 mm <sup>2</sup> /s
Viscosity index	110
Pour point	-37 °C
Four-ball tester: wear characteristics	0.6 mm
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months

## Summit Lubrication

Your expert in specialty lubricants. Since 1982, we have partnered with you to bring you the right solution and advanced lubrication technologies. With over 500 products, from air and gas compressor oils to refrigeration oils, we develop top-of-the-line products tailored to your specific needs. Your success is our success.

Summit Lubrication a brand of Klüber Lubrication NA LP /  
9010 County Road 2120, Tyler, TX 75707 /  
Phone: +1 800 749 5823 / [www.klsummit.com](http://www.klsummit.com)

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication NA LP. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication NA LP and if source is indicated and voucher copy is forwarded.